



(PLATFORM NOT SHOWN IN THESE VIEWS)

GENERAL SPECIFICATIONS

QUANTITY: ONE (1)  
MODEL: AGI-150 RL  
MAXIMUM FLOW RATE: 150 GPM  
STATIC CAPACITY: 202.5 GALLONS  
RETENTION TIME: 81 SEC  
TYPE: SINGLE WALL, ABOVE-GROUND  
MATERIAL: 10 GA 304 STAINLESS STEEL  
BUILT IN ACCORDANCE WITH U.L. 1D42

NOTES

STANDARD CONTROL PANEL OPERATES ON  
208V-3Ø + NEUTRAL SERVICE VOLTAGE – OPTIONAL  
PANELS AVAILABLE

GEAR MOTOR RATED AT 0.44 FLA, 115V – 60 Hz

IMMERSION HEATERS OPERATE AT 208V

ALL ELECTRICAL AND PLUMBING CONNECTIONS ARE  
SUBJECT TO LOCAL CODES

HIGHLAND TANK OFFERS A WIDE VARIETY OF OPTIONS  
AND CUSTOMIZATIONS TO ACCOMMODATE PROJECT  
CONDITIONS – CONTACT HIGHLAND TANK FOR MORE  
INFORMATION

RIGHT-TO-LEFT FLOW SHOWN  
LEFT-TO-RIGHT FLOW AVAILABLE

CUSTOMER APPROVAL

THE CUSTOMER HAS REVIEWED THIS  
DRAWING AND VERIFIED THE ACCURACY OF  
ALL INFORMATION AND DIMENSIONS.

SIGNED: \_\_\_\_\_

DATE: \_\_\_\_\_

NOTE:  
ALL RIGHTS RESERVED. THIS DRAWING, OR ANY PART THEREOF, MUST NOT  
BE REPRODUCED IN ANY FORM WITHOUT WRITTEN PERMISSION FROM  
HIGHLAND TANK. UNLESS OTHERWISE NOTED, HIGHLAND TANK SHALL BE  
RESPONSIBLE ONLY FOR ITEMS INDICATED ON THIS FABRICATION DRAWING.  
THE CUSTOMER IS RESPONSIBLE FOR VERIFYING THE CORRECTNESS OF  
THE TYPE, SIZE, AND LOCATION OF ALL FITTINGS, ACCESSORIES, AND  
COATINGS SHOWN ON THIS DRAWING.



GreaseStopper® AUTOMATIC GREASE INTERCEPTOR  
AGI-150 RL

CUSTOMER: \_\_\_\_\_

PROJECT: \_\_\_\_\_

QUOTE NO.: \_\_\_\_\_ ORDER: \_\_\_\_\_

SCALE: DATE: DWG. BY: DWG. NO:  
NTS 1/2/19 MGS AGI-150 RL

DIMENSION TOLERANCE: ± 1"