



GENERAL SPECIFICATIONS

QUANTITY: ONE (1)
MODEL: AGI-15 WH RL
MAXIMUM FLOW RATE: 15 GPM
STATIC CAPACITY: 9.2 GALLONS
RETENTION TIME: 36.8 SEC
TYPE: SINGLE WALL, ABOVE-GROUND
MATERIAL: 14 GA 304 STAINLESS STEEL
BUILT IN ACCORDANCE WITH U.L. 1D42

NOTES

DIGITAL TIMER MUST BE PLUGGED INTO A DEDICATED 20 AMP GROUND FAULT CIRCUIT INTERRUPTER (GFCI) RECEPTACLE

GEAR MOTOR RATED AT 0.44 FLA, 115V - 60 Hz

IMMERSION HEATERS RATED AT 1,500W, 115V

ALL ELECTRICAL AND PLUMBING CONNECTIONS ARE SUBJECT TO LOCAL CODES

HIGHLAND TANK OFFERS A WIDE VARIETY OF OPTIONS AND CUSTOMIZATIONS TO ACCOMMODATE PROJECT CONDITIONS - CONTACT HIGHLAND TANK FOR MORE INFORMATION

THIS DRAWING IS SUBJECT TO CHANGE AT THE DISCRETION OF THE MANUFACTURER. CONTACT HIGHLAND TANK FOR THE MOST UP-TO-DATE INFORMATION AND DRAWINGS OF OUR PRODUCTS.



Highland Tank®

GreaseStopper® AUTOMATIC GREASE INTERCEPTOR
AGI-15 WH RL

CUSTOMER:
PROJECT:

QUOTE NO.:
SCALE: NTS DATE: 1/20/18 DWG. BY: MGS DWG. NO.: AGI-15 WH RL

DIMENSION TOLERANCE: ± 1"