

GENERAL SPECIFICATIONS

QUANTITY: ONE (1)
MODEL: AGI-20 WH RL
MAXIMUM FLOW RATE: 20 GPM
STATIC CAPACITY: 12.6 GALLONS
RETENTION TIME: 37.8 SEC
TYPE: SINGLE WALL, ABOVE-GROUND
MATERIAL: 14 GA 304 STAINLESS STEEL
BUILT IN ACCORDANCE WITH U.L. 1D42

NOTES

DIGITAL TIMER MUST BE PLUGGED INTO A DEDICATED 20 AMP GROUND FAULT
CIRCUIT INTERRUPTER (GFCI) RECEPTACLE


GEAR MOTOR RATED AT 0.44 FLA, 115V - 60 Hz

IMMERSION HEATERS RATED AT 1,500W, 115V

ALL ELECTRICAL AND PLUMBING CONNECTIONS ARE SUBJECT TO LOCAL CODES

HIGHLAND TANK OFFERS A WIDE VARIETY OF OPTIONS AND CUSTOMIZATIONS TO
ACCOMMODATE PROJECT CONDITIONS - CONTACT HIGHLAND TANK FOR MORE
INFORMATION

THIS DRAWING IS SUBJECT TO CHANGE AT THE DISCRETION
OF THE MANUFACTURER. CONTACT HIGHLAND TANK FOR
THE MOST UP-TO-DATE INFORMATION AND DRAWINGS OF
OUR PRODUCTS.

**Highland Tank®**

GreaseStopper® AUTOMATIC GREASE INTERCEPTOR

AGI-20 WH RL

CUSTOMER:
PROJECT:

QUOTE NO.:
SCALE: DATE: DWG. BY: DWG. NO.:
NTS 1/20/18 MGS

ORDER:
AGI-20 WH RL

NOTE:
ALL RIGHTS RESERVED. THIS DRAWING, OR ANY PART THEREOF, MUST NOT
BE REPRODUCED IN ANY FORM WITHOUT WRITTEN PERMISSION FROM
HIGHLAND TANK. UNLESS OTHERWISE NOTED, HIGHLAND TANK SHALL BE
RESPONSIBLE ONLY FOR ITEMS INDICATED ON THIS FABRICATION DRAWING.
THE CUSTOMER IS RESPONSIBLE FOR VERIFYING THE CORRECTNESS OF
THE TYPE, SIZE, AND LOCATION OF ALL FITTINGS, ACCESSORIES, AND
COATINGS SHOWN ON THIS DRAWING.