



## GENERAL SPECIFICATIONS

QUANTITY: ONE (1)  
 MODEL: MGI-20L  
 MATERIAL: 10 GA CARBON STEEL  
 SINGLE-WALL CONSTRUCTION  
 SURFACE PREP: SSPC-SP 10 BLAST ALL SURFACES  
 INT. & EXT. COATING: POLYURETHANE  
 MAXIMUM FLOW RATE: 20 GPM  
 STATIC WATER CAPACITY: 18 GAL  
 GREASE HOLDING CAPACITY: 40 LBS  
 APPROXIMATE DRY WEIGHT: 175 LBS

## NOTES:

STANDARD TANK MATERIAL IS COATED  
 CARBON STEEL - STAINLESS STEEL  
 CONSTRUCTION IS AVAILABLE.

DRAWING SHOWS STANDARD TANK HEIGHT.  
 CUSTOMER MUST SPECIFY ACTUAL  
 HEIGHT DIMENSION REQUIRED.

ALL PLUMBING CONNECTIONS MUST COMPLY  
 WITH LOCAL CODES AND REGULATIONS.

## CUSTOMER APPROVAL

THE CUSTOMER HAS REVIEWED THIS  
 DRAWING AND VERIFIED THE ACCURACY OF  
 ALL INFORMATION AND DIMENSIONS.

SIGNED: \_\_\_\_\_

DATE: \_\_\_\_\_



## REVISIONS



**Highland Tank**<sup>®</sup>

MANUAL GREASE INTERCEPTOR  
 MGI-20L

CUSTOMER: \_\_\_\_\_

PROJECT: \_\_\_\_\_

QUOTE NO: \_\_\_\_\_

SCALE: \_\_\_\_\_

DATE: 10/17/12

DWG BY: MGS

DWG NO: \_\_\_\_\_

CHK'D BY: \_\_\_\_\_

MGI-20L

DIMENSION TOLERANCE: ± 1"

NOTE:  
 ALL RIGHTS RESERVED. THIS DRAWING, OR ANY PART THEREOF, MUST NOT  
 BE REPRODUCED IN ANY FORM WITHOUT WRITTEN PERMISSION FROM  
 HIGHLAND TANK. UNLESS OTHERWISE NOTED, HIGHLAND TANK SHALL BE  
 RESPONSIBLE ONLY FOR ITEMS INDICATED ON THIS FABRICATION DRAWING.  
 THE CUSTOMER IS RESPONSIBLE FOR VERIFYING THE CORRECTNESS OF  
 THE TYPE, SIZE, AND LOCATION OF ALL FITTINGS, ACCESSORIES, AND  
 COATINGS SHOWN ON THIS DRAWING.