

C OUTLET	<u>GENERAL</u> <u>SPECIFICATIONS</u> QUANTITY: ONE (1) MODEL: AGI-35 FM MAXIMUM FLOW RATE: 35 GPM STATIC CAPACITY: 37.9 GALLONS GREASE HOLDING CAPACITY: 288 LBS RETENTION TIME: 65 SEC TYPE: SINGLE WALL, UNDERGROUND MATERIAL: 10 GA 304 STAINLESS STEEL BUILT IN ACCORDANCE WITH U.L. 1D42 <u>NOTES</u> DRAWING SHOWS STANDARD TANK HEIGHT DIMENSION FROM INLET/OUTLET FITTINGS TO FINISHED FLOOR – CUSTOMER MUST SPECIFY HEIGHT DIMENSION MODIFICATIONS REQUIRED TO MEET PROJECT PLUMBING CONDITIONS DIGITAL TIMER MUST BE PLUGGED INTO A DEDICATED 20 AMP GROUND FAULT CIRCUIT INTERRUPTER (GFCI) RECEPTACLE GEAR MOTOR RATED AT 0.44 FLA, 115V – 60 Hz IMMERSION HEATERS RATED AT 1,500W, 115V ALL ELECTRICAL AND PLUMBING CONNECTIONS ARE SUBJECT TO LOCAL CODES HIGHLAND TANK OFFERS A WIDE VARIETY OF OPTIONS AND CUSTOMIZATIONS TO ACCOMMODATE PROJECT CONDITIONS – CONTACT HIGHLAND TANK FOR MORE INFORMATION
/- FINISHED GRADE	CUSTOMER APPROVAL THE CUSTOMER HAS REVIEWED THIS DRAWING AND VERIFIED THE ACCURACY OF ALL INFORMATION AND DIMENSIONS. SIGNED:
	DATE: NDTE: ALL RIGHTS RESERVED. THIS DRAWING, DR ANY PART THEREDF, MUST NDT BE REPRODUCED IN ANY FORM VITHOUT WRITTEN PERMISSION FROM HIGHLAND TAMK, UNLESS OTHERVISE NOTED IN THIS FABRICATION DRAWING. THE CUSTOMER IS RESPONSIBLE FOR VERIFYING THE CORRECTNESS OF THE TYPE, SIZE, AND LOCATION OF ALL FITTINGS, ACCESSORIES, AND COATINGS SHOWN ON THIS DRAWING. WIGHLAND HIGHLAND FOR TARAK
JUTLET PIPING & VENT BY INSTALLER IC DUTLET	GreaseStopper®AUTOMATIC GREASE INTERCEPTOR AGI-35 FM CUSTOMER:
DIMENSION TOLERANCE: ± 1"	PROJECT: QUOTE NO.: SCALE: DATE: DWG. BY: DWG. NO.: NTS 1/20/18 MGS AGI-35 FM