

- TWIST-LOCK	GENERAL SPECIFICATIONS QUANTITY: ONE (1) MODEL: AGI-35 WH RL MAXIMUM FLOW RATE: 35 GPM STATIC CAPACITY: 43.5 GALLONS RETENTION TIME: 74.6 SEC TYPE: SINGLE WALL, ABOVE-GROUND MATERIAL: 10 GA 304 STAINLESS STEEL BUILT IN ACCORDANCE WITH U.L. 1D42 <u>NOTES</u> DIGITAL TIMER MUST BE PLUGGED INTO A DEDICATED 20 AMP GROUND FAULT CIRCUIT INTERRUPTER (GFCI) RECEPTACLE GEAR MOTOR RATED AT 0.44 FLA, 115V – 60 Hz IMMERSION HEATERS RATED AT 1,500W, 115V ALL ELECTRICAL AND PLUMBING CONNECTIONS ARE SUBJECT TO LOCAL CODES HIGHLAND TANK OFFERS A WIDE VARIETY OF OPTIONS AND CUSTOMIZATIONS TO ACCOMMODATE PROJECT CONDITIONS – CONTACT HIGHLAND TANK FOR MORE INFORMATION
CONNECTOR	
	THIS DRAWING IS SUBJECT TO CHANGE AT THE DISCRETION OF THE MANUFACTURER. CONTACT HIGHLAND TANK FOR THE MOST UP-TO-DATE INFORMATION AND DRAWINGS OF OUR PRODUCTS. NUTE: ALL RIGHTS RESERVED. THIS DRAWING, DR ANY PART THEREDF, MUST NOT DE DEBRINGED THE ANY FORM WITHOUT WEITTEN DEBRISTING FORM
/	BE REPRODUCED IN ANY FORM WITHOUT WRITTEN PERMISSION FROM HIGHLAND TANK, UNLESS DIHERVISE NOTED, HIGHLAND TANK SHALL BE RESPONSIBLE DNLY FOR ITEMS INDICATED DN THIS FABRICATION DRAVING. THE CUSTOMER IS RESPONSIBLE FOR VERIFYING THE CORRECTNESS OF THE TYPE, SIZE, AND LOCATION OF ALL FITTINGS, ACCESSORIES, AND CONTINUES SUMMAN DN THE PRAVIDUE.
	COATINGS SHOWN ON THIS DRAVING.
	GreaseStopper $^{\textcircled{B}}$ AUTOMATIC GREASE INTERCEPTOR
	AGI-35 WH RL
	CUSTOMER: PROJECT:
	QUOTE NO.:
DIMENSION TOLERANCE: ± 1"	scale: NTS 1/20/18 MGS AGI-35 WH RL