



GENERAL SPECIFICATIONS

QUANTITY: ONE (1)
MODEL: AGI-400 RL
MAXIMUM FLOW RATE: 400 GPM
STATIC CAPACITY: 468.7 GALLONS
RETENTION TIME: 70.3 SEC
TYPE: SINGLE WALL, ABOVE-GROUND
MATERIAL: 10 GA 304 STAINLESS STEEL
BUILT IN ACCORDANCE WITH U.L. 1D42

NOTES

STANDARD CONTROL PANEL OPERATES ON
208V-3Ø + NEUTRAL SERVICE VOLTAGE – OPTIONAL
PANELS AVAILABLE

GEAR MOTOR RATED AT 0.44 FLA, 115V – 60 Hz

IMMERSION HEATERS OPERATE AT 208V

ALL ELECTRICAL AND PLUMBING CONNECTIONS ARE
SUBJECT TO LOCAL CODES

HIGHLAND TANK OFFERS A WIDE VARIETY OF OPTIONS
AND CUSTOMIZATIONS TO ACCOMMODATE PROJECT
CONDITIONS – CONTACT HIGHLAND TANK FOR MORE
INFORMATION

RIGHT-TO-LEFT FLOW SHOWN
LEFT-TO-RIGHT FLOW AVAILABLE

CUSTOMER APPROVAL

THE CUSTOMER HAS REVIEWED THIS
DRAWING AND VERIFIED THE ACCURACY OF ALL
INFORMATION AND DIMENSIONS.

SIGNED: _____

DATE: _____

NOTE:
ALL RIGHTS RESERVED. THIS DRAWING, OR ANY PART THEREOF, MUST NOT
BE REPRODUCED IN ANY FORM WITHOUT WRITTEN PERMISSION FROM
HIGHLAND TANK. UNLESS OTHERWISE NOTED, HIGHLAND TANK SHALL BE
RESPONSIBLE ONLY FOR ITEMS INDICATED ON THIS FABRICATION DRAWING.
THE CUSTOMER IS RESPONSIBLE FOR VERIFYING THE CORRECTNESS OF
THE TYPE, SIZE, AND LOCATION OF ALL FITTINGS, ACCESSORIES, AND
COATINGS SHOWN ON THIS DRAWING.



Highland Tank®

GreaseStopper® AUTOMATIC GREASE INTERCEPTOR
AGI-400 RL

CUSTOMER: _____

PROJECT: _____

QUOTE NO.: _____

ORDER: _____

SCALE: DATE: DWG. BY: DWG. NO.:
NTS 1/2/19 MGS AGI-400 RL

DIMENSION TOLERANCE: ± 1"

(PLATFORM NOT SHOWN IN THESE VIEWS)