



(PLATFORM NOT SHOWN IN THESE VIEWS)

CUSTOMER APPROVAL

THE CUSTOMER HAS REVIEWED THIS DRAWING AND VERIFIED THE ACCURACY OF ALL INFORMATION AND DIMENSIONS.

SIGNED: \_\_\_\_\_

DATE: \_\_\_\_\_

NOTES

STANDARD CONTROL PANEL OPERATES ON 208V-3Ø + NEUTRAL  
SERVICE VOLTAGE – OPTIONAL PANELS AVAILABLE

GEAR MOTOR RATED AT 0.44 FLA, 115V – 60 Hz

IMMERSION HEATERS OPERATE AT 208V

ALL ELECTRICAL AND PLUMBING CONNECTIONS ARE SUBJECT TO LOCAL CODES

HIGHLAND TANK OFFERS A WIDE VARIETY OF OPTIONS AND CUSTOMIZATIONS TO ACCOMMODATE PROJECT CONDITIONS – CONTACT HIGHLAND TANK FOR MORE INFORMATION

GENERAL SPECIFICATIONS

QUANTITY: ONE (1)  
MODEL: AGI-500 LR  
MAXIMUM FLOW RATE: 500 GPM  
STATIC CAPACITY: 552 GALLONS  
RETENTION TIME: 66.3 SEC  
TYPE: SINGLE WALL, ABOVE-GROUND  
MATERIAL: 10 GA 304 STAINLESS STEEL  
BUILT IN ACCORDANCE WITH U.L. 1D42

LEFT-TO-RIGHT FLOW SHOWN  
RIGHT-TO-LEFT FLOW AVAILABLE



**Highland Tank**<sup>®</sup>

GreaseStopper<sup>®</sup> AUTOMATIC GREASE INTERCEPTOR

AGI-500 LR

CUSTOMER: \_\_\_\_\_

PROJECT: \_\_\_\_\_

QUOTE NO.: \_\_\_\_\_

SCALE: \_\_\_\_\_ DATE: 1/2/19 DWG. BY: MGS DWG. NO.: AGI-500 LR

DIMENSION TOLERANCE: ± 1"