



(PLATFORM NOT SHOWN IN THESE VIEWS)

### GENERAL SPECIFICATIONS

QUANTITY: ONE (1)  
MODEL: AGI-500 RL  
MAXIMUM FLOW RATE: 500 GPM  
STATIC CAPACITY: 552 GALLONS  
RETENTION TIME: 66.3 SEC  
TYPE: SINGLE WALL, ABOVE-GROUND  
MATERIAL: 10 GA 304 STAINLESS STEEL  
BUILT IN ACCORDANCE WITH U.L. 1D42

RIGHT-TO-LEFT FLOW SHOWN  
LEFT-TO-RIGHT FLOW AVAILABLE

### CUSTOMER APPROVAL

THE CUSTOMER HAS REVIEWED THIS  
DRAWING AND VERIFIED THE ACCURACY OF  
ALL INFORMATION AND DIMENSIONS.

SIGNED: \_\_\_\_\_

DATE: \_\_\_\_\_

### NOTES

STANDARD CONTROL PANEL OPERATES ON 208V-3Ø + NEUTRAL  
SERVICE VOLTAGE - OPTIONAL PANELS AVAILABLE

GEAR MOTOR RATED AT 0.44 FLA, 115V - 60 Hz

IMMERSION HEATERS OPERATE AT 208V

ALL ELECTRICAL AND PLUMBING CONNECTIONS ARE SUBJECT TO LOCAL CODES

HIGHLAND TANK OFFERS A WIDE VARIETY OF OPTIONS AND CUSTOMIZATIONS TO  
ACCOMMODATE PROJECT CONDITIONS - CONTACT HIGHLAND TANK FOR MORE  
INFORMATION



# Highland Tank®

GreaseStopper® AUTOMATIC GREASE INTERCEPTOR  
AGI-500 RL

CUSTOMER: \_\_\_\_\_

PROJECT: \_\_\_\_\_

QUOTE NO.: \_\_\_\_\_

SCALE: \_\_\_\_\_

DATE: 1/2/19

DWG. BY: MGS

DWG. NO.: \_\_\_\_\_

ORDER: \_\_\_\_\_

DIMENSION TOLERANCE: ± 1"

NTS

1/2/19

MGS

AGI-500 RL

NOTE:  
ALL RIGHTS RESERVED. THIS DRAWING, OR ANY PART THEREOF, MUST NOT  
BE REPRODUCED IN ANY FORM WITHOUT WRITTEN PERMISSION FROM  
HIGHLAND TANK. UNLESS OTHERWISE NOTED, HIGHLAND TANK SHALL BE  
RESPONSIBLE ONLY FOR ITEMS INDICATED ON THIS FABRICATION DRAWING.  
THE CUSTOMER IS RESPONSIBLE FOR VERIFYING THE CORRECTNESS OF  
THE TYPE, SIZE, AND LOCATION OF ALL FITTINGS, ACCESSORIES, AND  
COATINGS SHOWN ON THIS DRAWING.