

DUTLET BAFFLE	GENERAL SPECIFICATIONS QUANTITY: DNE (1) MDDEL: HTM-ESP-INT-50 AG MAXIMUM FLOW RATE: 50 GPM TDTAL CAPACITY: 358 GALLONS INTERCEPTOR STATIC CAPACITY: 200 GALLONS MEDIA CHAMBER STATIC CAPACITY: 69 GALLONS DIL CAPACITY: 45 GALLONS TYPE: SINGLE WALL, ABOVE GROUND MATERIAL: 10 GA CARBON STEEL WITH 7 GA BOTTOM CONTINUOUS WELD INTERIOR AND EXTERIOR SURFACES SSPC-SP 6 BLAST INTERIOR SURFACES EXT. CDATING: CHEMPRIME 3001 - 3-6 MILS CHEMLINE 3300 WHITE - 2-3 MILS INT. CDATING: CHEMLINE 4200PW - 15 MILS NOTE: UNIT TO SHIP WITH PLASTIC PLUGS IN ALL FITTINGS NOT OTHERWISE NOTED
4" SCH 40 STEEL PIPE 4" FNPT DUTLET	
34″	HIGHLAND TANK. UNLESS DTHERVISE NOTED, HIGHLAND TANK SHALL BE RESPONSIBLE DNLY FOR ITHEN SIDICATED ON THIS FABRICATION DRAVING. THE CUSTOMER IS RESPONSIBLE FOR VERIFYING THE CORRECTNESS OF THE TYPE, SIZE, AND LICATION OF ALL FITTINGS, ACCESSORIES, AND COATINGS SHOWN ON THIS DRAVING.
	50 GPM ELEVATOR SUMP INTERCEPTOR HTM—ESP—INT—50 AG customer: project:
<u>r</u>	QUOTE NO.: SCALE: NTS 2/14/25 MGS ESP-INT-50 AG