



**GENERAL SPECIFICATIONS**  
QUANTITY: ONE (1)  
MODEL: AGI-50 FM  
MAXIMUM FLOW RATE: 50 GPM  
STATIC CAPACITY: 49.9 GALLONS  
GREASE HOLDING CAPACITY: 284 LBS  
RETENTION TIME: 59.9 SEC  
TYPE: SINGLE WALL, UNDERGROUND  
MATERIAL: 10 GA 304 STAINLESS STEEL  
BUILT IN ACCORDANCE WITH U.L. 1D42

**NOTES**  
DRAWING SHOWS STANDARD TANK HEIGHT DIMENSION FROM INLET/OUTLET FITTINGS TO FINISHED FLOOR – CUSTOMER MUST SPECIFY HEIGHT DIMENSION MODIFICATIONS REQUIRED TO MEET PROJECT PLUMBING CONDITIONS  
  
DIGITAL TIMER MUST BE PLUGGED INTO A DEDICATED 20 AMP GROUND FAULT CIRCUIT INTERRUPTER (GFCI) RECEPTACLE  
  
GEAR MOTOR RATED AT 0.44 FLA, 115V – 60 Hz  
  
IMMERSION HEATERS RATED AT 1,500W, 115V  
  
ALL ELECTRICAL AND PLUMBING CONNECTIONS ARE SUBJECT TO LOCAL CODES  
  
HIGHLAND TANK OFFERS A WIDE VARIETY OF OPTIONS AND CUSTOMIZATIONS TO ACCOMMODATE PROJECT CONDITIONS – CONTACT HIGHLAND TANK FOR MORE INFORMATION

**CUSTOMER APPROVAL**  
  
THE CUSTOMER HAS REVIEWED THIS DRAWING AND VERIFIED THE ACCURACY OF ALL INFORMATION AND DIMENSIONS.  
  
SIGNED: \_\_\_\_\_  
DATE: \_\_\_\_\_

NOTE:  
ALL RIGHTS RESERVED. THIS DRAWING, OR ANY PART THEREOF, MUST NOT BE REPRODUCED IN ANY FORM WITHOUT WRITTEN PERMISSION FROM HIGHLAND TANK. UNLESS OTHERWISE NOTED, HIGHLAND TANK SHALL BE RESPONSIBLE ONLY FOR ITEMS INDICATED ON THIS FABRICATION DRAWING. THE CUSTOMER IS RESPONSIBLE FOR VERIFYING THE CORRECTNESS OF THE TYPE, SIZE, AND LOCATION OF ALL FITTINGS, ACCESSORIES, AND COATINGS SHOWN ON THIS DRAWING.

**Highland Tank®**

GreaseStopper® AUTOMATIC GREASE INTERCEPTOR  
**AGI-50 FM**

CUSTOMER: \_\_\_\_\_

PROJECT: \_\_\_\_\_

QUOTE NO.: \_\_\_\_\_

ORDER: \_\_\_\_\_

SCALE: \_\_\_\_\_ DATE: 1/20/18 DWG. BY: MGS DWG. NO.: \_\_\_\_\_