



(PLATFORM NOT SHOWN IN THESE VIEWS)

NOTES

STANDARD CONTROL PANEL OPERATES ON 208V-3 ϕ + NEUTRAL
SERVICE VOLTAGE - OPTIONAL PANELS AVAILABLE

GEAR MOTOR RATED AT 0.44 FLA, 115V - 60 Hz

IMMERSION HEATERS OPERATE AT 208V

ALL ELECTRICAL AND PLUMBING CONNECTIONS ARE SUBJECT TO LOCAL CODES

HIGHLAND TANK OFFERS A WIDE VARIETY OF OPTIONS AND CUSTOMIZATIONS TO
ACCOMMODATE PROJECT CONDITIONS - CONTACT HIGHLAND TANK FOR MORE
INFORMATION

GENERAL SPECIFICATIONS

QUANTITY: ONE (1)
MODEL: AGI-600 LR
MAXIMUM FLOW RATE: 600 GPM
STATIC CAPACITY: 658 GALLONS
RETENTION TIME: 65.8 SEC
TYPE: SINGLE WALL, ABOVE-GROUND
MATERIAL: 10 GA 304 STAINLESS STEEL
BUILT IN ACCORDANCE WITH U.L. 1D42

LEFT-TO-RIGHT FLOW SHOWN
RIGHT-TO-LEFT FLOW AVAILABLE



Highland Tank®

GreaseStopper® AUTOMATIC GREASE INTERCEPTOR
AGI-600 LR

CUSTOMER:

PROJECT:

QUOTE NO.:

SCALE:

DATE:

DWG. BY:

DWG. NO.:

ORDER:

DIMENSION TOLERANCE: \pm 1"

NTS

1/2/19

MGS

AGI-600 LR

CUSTOMER APPROVAL

THE CUSTOMER HAS REVIEWED THIS
DRAWING AND VERIFIED THE ACCURACY OF
ALL INFORMATION AND DIMENSIONS.

SIGNED:

DATE:

NOTE:
ALL RIGHTS RESERVED. THIS DRAWING, OR ANY PART THEREOF, MUST NOT
BE REPRODUCED IN ANY FORM WITHOUT WRITTEN PERMISSION FROM
HIGHLAND TANK. UNLESS OTHERWISE NOTED, HIGHLAND TANK SHALL BE
RESPONSIBLE ONLY FOR ITEMS INDICATED ON THIS FABRICATION DRAWING.
THE CUSTOMER IS RESPONSIBLE FOR VERIFYING THE CORRECTNESS OF
THE TYPE, SIZE, AND LOCATION OF ALL FITTINGS, ACCESSORIES, AND
COATINGS SHOWN ON THIS DRAWING.