

GENERAL SPECIFICATIONS


QUANTITY: ONE (1)
MODEL: AGI-75 IF
MAXIMUM FLOW RATE: 75 GPM
STATIC WATER CAPACITY: 74.8 GAL
GREASE HOLDING CAPACITY: 455 LBS
RETENTION TIME: 59.8 SEC
MATERIAL: 10 GA 304 STAINLESS STEEL
BUILT IN ACCORDANCE WITH U.L. 1D42

NOTES

- AGI MUST BE PLUGGED INTO A 20 AMP GROUND FAULT INTERRUPTER (GFCI) RECEPTACLE
- GEAR MOTOR RATED AT 0.44 FLA, 115V, 60 Hz
- IMMERSION HEATERS - 1500W EA. 115V
- ALL ELECTRICAL AND PLUMBING CONNECTIONS ARE SUBJECT TO LOCAL CODES

NOTE:
ALL RIGHTS RESERVED. THIS DRAWING, OR ANY PART THEREOF, MUST NOT BE REPRODUCED IN ANY FORM WITHOUT WRITTEN PERMISSION FROM HIGHLAND TANK. UNLESS OTHERWISE NOTED, HIGHLAND TANK SHALL BE RESPONSIBLE ONLY FOR ITEMS INDICATED ON THIS FABRICATION DRAWING. THE CUSTOMER IS RESPONSIBLE FOR VERIFYING THE CORRECTNESS OF THE TYPE, SIZE, AND LOCATION OF ALL FITTINGS, ACCESSORIES, AND COATINGS SHOWN ON THIS DRAWING.

THIS DRAWING IS SUBJECT TO CHANGE AT THE DISCRETION OF THE MANUFACTURER. CONTACT HIGHLAND TANK FOR THE MOST UP-TO-DATE INFORMATION AND DRAWINGS OF OUR PRODUCTS.



Highland Tank®
MFG CO.

GreaseStopper® AUTOMATIC GREASE INTERCEPTOR
AGI-75 IF

CUSTOMER:

PROJECT:

QUOTE NO.:

ORDER:

SCALE: NTS

DATE: 4/21/25

DWG. BY: MGS

DWG. NO.: AGI-75 IF

DIMENSION TOLERANCE: ± 1"