



GENERAL SPECIFICATIONS

QUANTITY: ONE (1)
 MODEL: MGI-75
 MAXIMUM FLOW RATE: 75 GPM
 STATIC CAPACITY: 76 GALLONS
 GREASE HOLDING CAPACITY: 150 LBS
 TYPE: SINGLE WALL, UNDERGROUND
 MATERIAL: 10 GA CARBON STEEL
 CONTINUOUS WELD INTERIOR AND EXTERIOR SEAMS
 SURFACE PREP: SSPC-SP 10 BLAST ALL SURFACES
 INT. & EXT. COATING: CHEMLINE 2240 - 15 MILS DFT

NOTES

STANDARD TANK MATERIAL IS COATED CARBON STEEL - STAINLESS STEEL CONSTRUCTION IS OPTIONAL

DRAWING SHOWS STANDARD TANK HEIGHT DIMENSION FROM INLET/OUTLET FITTINGS TO FINISHED FLOOR - CUSTOMER MUST SPECIFY HEIGHT DIMENSION MODIFICATIONS REQUIRED TO MEET PROJECT PLUMBING CONDITIONS

STANDARD TANK LID IS RATED FOR PEDESTRIANS ONLY - H-20 TRAFFIC RATED LIDS ARE OPTIONAL

CUSTOMER APPROVAL

THE CUSTOMER HAS REVIEWED THIS DRAWING AND VERIFIED THE ACCURACY OF ALL INFORMATION AND DIMENSIONS.

SIGNED: _____
 DATE: _____

NOTE:
 ALL RIGHTS RESERVED. THIS DRAWING, OR ANY PART THEREOF, MUST NOT BE REPRODUCED IN ANY FORM WITHOUT WRITTEN PERMISSION FROM HIGHLAND TANK. UNLESS OTHERWISE NOTED, HIGHLAND TANK SHALL BE RESPONSIBLE ONLY FOR ITEMS INDICATED ON THIS FABRICATION DRAWING. THE CUSTOMER IS RESPONSIBLE FOR VERIFYING THE CORRECTNESS OF THE TYPE, SIZE, AND LOCATION OF ALL FITTINGS, ACCESSORIES, AND COATINGS SHOWN ON THIS DRAWING.



MANUAL GREASE INTERCEPTOR
MGI-75

CUSTOMER: _____
 PROJECT: _____
 QUOTE NO.: _____
 ORDER: _____