



(PLATFORM NOT SHOWN IN THESE VIEWS)

CUSTOMER APPROVAL

THE CUSTOMER HAS REVIEWED THIS DRAWING AND VERIFIED THE ACCURACY OF ALL INFORMATION AND DIMENSIONS.

SIGNED: _____

DATE: _____

NOTES

STANDARD CONTROL PANEL OPERATES ON 208V-3Ø + NEUTRAL SERVICE VOLTAGE – OPTIONAL PANELS AVAILABLE

GEAR MOTOR RATED AT 0.44 FLA, 115V – 60 Hz

IMMERSION HEATERS OPERATE AT 208V

ALL ELECTRICAL AND PLUMBING CONNECTIONS ARE SUBJECT TO LOCAL CODES

HIGHLAND TANK OFFERS A WIDE VARIETY OF OPTIONS AND CUSTOMIZATIONS TO ACCOMMODATE PROJECT CONDITIONS – CONTACT HIGHLAND TANK FOR MORE INFORMATION

GENERAL SPECIFICATIONS

QUANTITY: ONE (1)

MODEL: AGI-800 LR

MAXIMUM FLOW RATE: 800 GPM

STATIC CAPACITY: 1,088 GALLONS

RETENTION TIME: 81.6 SEC

TYPE: SINGLE WALL, ABOVE-GROUND

MATERIAL: 10 GA 304 STAINLESS STEEL

BUILT IN ACCORDANCE WITH U.L. 1D42

LEFT-TO-RIGHT FLOW SHOWN
RIGHT-TO-LEFT FLOW AVAILABLE

HIGHLAND TANK

MFG. CO.

Highland Tank®

GreaseStopper® AUTOMATIC GREASE INTERCEPTOR

AGI-800 LR

CUSTOMER: _____

PROJECT: _____

QUOTE NO.: _____

SCALE: _____ DATE: 1/2/19 DWG. BY: MGS DWG. NO.: AGI-800 LR

DIMENSION TOLERANCE: ± 1"