



CUSTOMER APPROVAL

THE CUSTOMER HAS REVIEWED THIS DRAWING AND VERIFIED THE ACCURACY OF ALL INFORMATION AND DIMENSIONS.

SIGNED: \_\_\_\_\_

DATE: \_\_\_\_\_

**NOTES**

STANDARD CONTROL PANEL OPERATES ON 208V-3Ø + NEUTRAL  
SERVICE VOLTAGE – OPTIONAL PANELS AVAILABLE

GEAR MOTOR RATED AT 0.44 FLA, 115V – 60 Hz

IMMERSION HEATERS OPERATE AT 208V

ALL ELECTRICAL AND PLUMBING CONNECTIONS ARE SUBJECT TO LOCAL CODES

HIGHLAND TANK OFFERS A WIDE VARIETY OF OPTIONS AND CUSTOMIZATIONS TO ACCOMMODATE PROJECT CONDITIONS – CONTACT HIGHLAND TANK FOR MORE INFORMATION

**GENERAL SPECIFICATIONS**

QUANTITY: ONE (1)  
MODEL: AGI-800 RL  
MAXIMUM FLOW RATE: 800 GPM  
STATIC CAPACITY: 1,088 GALLONS  
RETENTION TIME: 81.6 SEC  
TYPE: SINGLE WALL, ABOVE-GROUND  
MATERIAL: 10 GA 304 STAINLESS STEEL  
BUILT IN ACCORDANCE WITH U.L. 1D42

RIGHT-TO-LEFT FLOW SHOWN  
LEFT-TO-RIGHT FLOW AVAILABLE



**Highland Tank®**  
GreaseStopper® AUTOMATIC GREASE INTERCEPTOR  
**AGI-800 RL**

CUSTOMER: \_\_\_\_\_

PROJECT: \_\_\_\_\_

QUOTE NO.: \_\_\_\_\_

ORDER: \_\_\_\_\_

SCALE: \_\_\_\_\_ DATE: 1/2/19 DWG. BY: MGS DWG. NO.: AGI-800 RL

DIMENSION TOLERANCE: ± 1"

NOTE:  
ALL RIGHTS RESERVED. THIS DRAWING, OR ANY PART THEREOF, MUST NOT BE REPRODUCED IN ANY FORM WITHOUT WRITTEN PERMISSION FROM HIGHLAND TANK. UNLESS OTHERWISE NOTED, HIGHLAND TANK SHALL BE RESPONSIBLE ONLY FOR ITEMS INDICATED ON THIS FABRICATION DRAWING. THE CUSTOMER IS RESPONSIBLE FOR VERIFYING THE CORRECTNESS OF THE TYPE, SIZE, AND LOCATION OF ALL FITTINGS, ACCESSORIES, AND COATINGS SHOWN ON THIS DRAWING.