

GENERAL SPECIFICATIONS

QUANTITY: ONE (1)
MODEL: HTM-ESP-INT-100 AG
MAXIMUM FLOW RATE: 100 GPM
TOTAL CAPACITY: 595 GALLONS
INTERCEPTOR STATIC CAPACITY: 296 GALLONS
MEDIA CHAMBER STATIC CAPACITY: 142 GALLONS
OIL CAPACITY: 53 GALLONS
TYPE: SINGLE WALL, ABOVE GROUND
MATERIAL: 10 GA CARBON STEEL WITH 7 GA BOTTOM
CONTINUOUS WELD INTERIOR AND EXTERIOR SEAMS
SURFACE PREP: SSPC-SP 10 BLAST INTERIOR SURFACES
SSPC-SP 6 BLAST EXTERIOR SURFACES
EXT. COATING: CHEMPRIME 3001 - 3-6 MILS
CHEMLINE 3300 WHITE - 2-3 MILS
INT. COATING: CHEMLINE 4200PW - 15 MILS

NOTE: UNIT TO SHIP WITH PLASTIC PLUGS IN ALL FITTINGS NOT OTHERWISE NOTED

CUSTOMER APPROVAL

THE CUSTOMER HAS REVIEWED THIS DRAWING AND VERIFIED THE ACCURACY OF ALL INFORMATION AND DIMENSIONS.

SIGNED: _____

DATE: _____

NOTE:
ALL RIGHTS RESERVED. THIS DRAWING, OR ANY PART THEREOF, MUST NOT BE REPRODUCED IN ANY FORM WITHOUT WRITTEN PERMISSION FROM HIGHLAND TANK. UNLESS OTHERWISE NOTED, HIGHLAND TANK SHALL BE RESPONSIBLE ONLY FOR ITEMS INDICATED ON THIS FABRICATION DRAWING. THE CUSTOMER IS RESPONSIBLE FOR VERIFYING THE CORRECTNESS OF THE TYPE, SIZE, AND LOCATION OF ALL FITTINGS, ACCESSORIES, AND COATINGS SHOWN ON THIS DRAWING.



100 GPM ELEVATOR SUMP INTERCEPTOR
HTM-ESP-INT-100 AG

CUSTOMER: _____
PROJECT: _____

QUOTE NO.: _____

SCALE: NTS	DATE: 2/14/25	DWG. BY: MGS	DWG. NO.: ESP-INT-100 AG
------------	---------------	--------------	--------------------------

