

	GENERAL SPECIFICATIONS QUANTITY: ONE (1) MODEL: AGI-100 FM MAXIMUM FLOW RATE: 100 GPM STATIC CAPACITY: 103.9 GALLONS GREASE HOLDING CAPACITY: 632 LBS RETENTION TIME: 62.3 SEC TYPE: SINGLE WALL, UNDERGROUND MATERIAL: 10 GA 304 STAINLESS STEEL BUILT IN ACCORDANCE WITH U.L. 1D42
4″ HC DUTLET	\underline{NOTES} drawing shows standard tank height dimension from inlet/outlet fittings to finished floor – customer must specify height dimension modifications required to meet project plumbing conditions
	DIGITAL TIMER MUST BE PLUGGED INTO A DEDICATED 20 AMP GROUND FAULT CIRCUIT INTERRUPTER (GFCI) RECEPTACLE
	GEAR MOTOR RATED AT 0.44 FLA, 115V – 60 Hz
	IMMERSION HEATERS RATED AT 1,500W, 115V
	ALL ELECTRICAL AND PLUMBING CONNECTIONS ARE SUBJECT TO LOCAL CODES
	HIGHLAND TANK OFFERS A WIDE VARIETY OF OPTIONS AND CUSTOMIZATIONS TO ACCOMMODATE PROJECT CONDITIONS – CONTACT HIGHLAND TANK FOR MORE INFORMATION
FINISHED GRADE	QUSTIDMER_APPRIDVAL
<u>م</u>	THE CUSTOMER HAS REVIEWED THIS DRAWING AND VERIFIED THE ACCURACY OF ALL INFORMATION AND DIMENSIONS. SIGNED: DATE:
	NDTE: ALL RIGHTS RESERVED. THIS DRAWING, DR ANY PART THEREDF, MUST NDT BE REPRODUCED IN ANY FORM WITHOUT WRITTEN PERMISSION FROM HIGHLAND TANK, UNLESS DTHERVISE NOTED, HIGHLAND TANK SHALL BE RESPONSIBLE DNLY FOR ITEMS INDICATED ON THIS FABRICATION DRAWING. THE CUSTOMER IS RESPONSIBLE FOR VERIFYING THE CORRECTNESS OF THE TYPE, SIZE, AND LOCATION OF ALL FITTINGS, ACCESSORIES, AND COATINGS SHOWN ON THIS DRAWING.
UTLET PIPING &	Highland Tank [®]
VENT BY INSTALLER 'HC DUTLET	GreaseStopper®AUTOMATIC GREASE INTERCEPTOR
	CUSTOMER:
	PROJECT: QUOTE NO.:
DIMENSION TOLERANCE: + 1"	NTS 1/20/18 MGS AGI-100 FM