GENERAL SPECIFICATIONS

NO. REQ'D: (1)
CAPACITY: 100 GALLONS
SPILL CAPACITY: 40 GALLONS

TYPE: RECTANGULAR, HT, ABOVEGROUND, SINGLEWALL

MATERIAL: MILD CARBON STEEL APPROX. WEIGHT: 600 LBS.

FLOW RATE: 5 GPM

GAUGE:

SHELL- 10 GA HEADS- 10 GA

SURFACE PREP: SSPC NO.10 BLAST ALL INTERIOR SURFACES SSPC NO.6 BLAST ALL EXTERIOR SURFACES

MATERIAL COATING: **THICKNESS** EXTERIOR - FINISH PAINT WHITE (3 MILS) INTERIOR- POLYURETHANE (15 MILS) **CONSTRUCTION:**

BUTT FIT & WELD ALL CORNERS IN & OUT

NOTES:

1. ALL INTERNAL MATERIAL IS 10 GA

(19)

(13)


(16)

(11)


- 2. ALL FITTINGS MUST SHIP W/ STEEL PLUGS INSTALLED
- 3. LIFTING LUGS DO NOT HAVE REINFORCING **PLATES**

(55)

(55)



PLAN



END VIEW

ALL RIGHTS RESERVED. THIS DRAWING OR ANY PART THEREOF MUST NOT BE REPRODUCED IN ANY FORM WITHOUT THE WRITTEN PERMISSION OF HIGHLAND TANK.

HIGHLAND TANK SHALL BE RESPONSIBLE ONLY FOR ITEMS INDICATED ON THIS FABRICATION DRAWING UNLESS OTHERWISE NOTED. CUSTOMER IS RESPONSIBLE FOR VERIFYING CORRECTNESS OF SIZE / LOCATION OF FITTINGS . ACCESSORIES & COATINGS SHOWN ON THIS DRAWING

ELEVATION

PROVIDED EQUIPMENT

- 1. 3"X3"X1/4" FLAT W/ 1/2" HOLE DRILLED IN CENTER (GROUNDING LUG)
- SEDIMENT CHAMBER
- 3. OIL WATER SEPARATOR CHAMBER
- 4. THREADED INLET
- 5. PVC INLET ELBOW PIPING
- 6. VELOCITY HEAD DIFFUSION BAFFLE 10GA
- 7. WEAR PLATE 1/4'
- 8. REMOVABLE PARALLEL CORRUGATED PLATE COALESCER (GALVANIZED_PLATES) 1" PLATE SPACING
- SLUDGE BAFFLE 10GA
- 10. PVC OUTLET DOWNCOMER PIPE
- 11. THREADED OUTLET
- 12. (2) PIECE COVER 10 GA
- 13. NÚTS & BOLTS W/ LARGE WING NUTS-TYP. (CORROSION RESISTANT)
- 14. GASKET MATERIAL (FOR ÉACH REMOVABLE COVER)
- 15. 3"ø NPT (CLEAN-OUT)
- 16. 2"ø NPT (FITTING FOR VENT)
- 17. 2"ø HALF COUPLING (DRAIN) W/ STEEL PLUG
- 18. 2"ø FULL COUPLING W/ 2"ø INTERNAL PVC PIPE

- 19. 2"ø HALF COUPLING (FITTING FOR LEVEL SENSOR)
 20. 1"ø 90 * ELBOW W/ 1" HALF COUPLING ON TOP
 WITH PVC RISER PIPE
- 21. 7 GA BRACING ACROSS TOP OF TANK W/ SENSOR & PUMP-OUT FITTINGS
- 22. LIFTING LUGS
- 23. 1"ø FERNCO COUPLING
- 24. HANDLES PER H.T. STANDARD
- 25. 1"ø COUPLING W/ PLUG

