



GENERAL SPECIFICATIONS

MODEL: AGI-125 FM
MATERIAL: 304 STAINLESS STEEL
2B FINISH
GAUGE OF MATERIAL: 10 GA
BUILT IN ACCORDANCE WITH U.L. 1D42
APPROX. DRY WEIGHT: 925 LBS
STATIC WATER CAPACITY: 124.7 GAL
MAXIMUM FLOW RATE: 125 GPM
GREASE HOLDING CAPACITY: ____ LBS
RETENTION TIME: 60 SEC

- NOTES
- AGI MUST BE PLUGGED INTO A 20 AMP GROUND FAULT INTERRUPTER (GFI) RECEPTACLE
 - GEAR MOTOR RATED AT 0.44 FLA, 115V, 60 Hz
 - IMMERSION HEATERS - 1500W EA. 115V
 - ALL ELECTRICAL AND PLUMBING CONNECTIONS ARE SUBJECT TO LOCAL CODES

CUSTOMER APPROVAL

THE CUSTOMER HAS REVIEWED THIS
DRAWING AND VERIFIED THE
ACCURACY OF ALL INFORMATION AND
DIMENSIONS.

SIGNED: _____

DATE: _____

REVISIONS			
<div>Highland Tank®</div>			
GreaseStopper® AUTOMATIC GREASE INTERCEPTOR AGI-125 FM			
CUSTOMER: _____			
PROJECT: _____			
QUOTE NO: _____ ORDER# _____			
SCALE: NTS	DATE: 1/16/13	DWG BY: MGS	DWG NO: AGI-125 FM