


GENERAL SPECIFICATIONS			
QUANTITY: ONE (1)			
MODEL: MGI-125			
MAXIMUM FLOW RATE: 125 GPM			
STATIC CAPACITY: 226 GALLONS			
GREASE HOLDING CAPACITY: 250 LBS			
TYPE: SINGLE WALL, UNDERGROUND			
MATERIAL: 10 GA CARBON STEEL			
CONTINUOUS WELD INTERIOR AND EXTERIOR SEAMS			
SURFACE PREP: SSPC-SP 10 BLAST ALL SURFACES			
INT. & EXT. COATING: CHEMLINE 2240 - 15 MILS DFT			
NOTES			
STANDARD TANK MATERIAL IS COATED CARBON STEEL - STAINLESS STEEL CONSTRUCTION IS OPTIONAL			
DRAWING SHOWS STANDARD TANK HEIGHT DIMENSION FROM INLET/OUTLET FITTINGS TO FINISHED FLOOR - CUSTOMER MUST SPECIFY HEIGHT DIMENSION MODIFICATIONS REQUIRED TO MEET PROJECT PLUMBING CONDITIONS			
STANDARD TANK LID IS RATED FOR PEDESTRIANS ONLY - H-20 TRAFFIC RATED LIDS ARE OPTIONAL			
CUSTOMER APPROVAL			
THE CUSTOMER HAS REVIEWED THIS DRAWING AND VERIFIED THE ACCURACY OF ALL INFORMATION AND DIMENSIONS.			
SIGNED: _____			
DATE: _____			
NOTE: ALL RIGHTS RESERVED. THIS DRAWING, OR ANY PART THEREOF, MUST NOT BE REPRODUCED IN ANY FORM WITHOUT WRITTEN PERMISSION FROM HIGHLAND TANK. UNLESS OTHERWISE NOTED, HIGHLAND TANK SHALL BE RESPONSIBLE ONLY FOR ITEMS INDICATED ON THIS FABRICATION DRAWING. THE CUSTOMER IS RESPONSIBLE FOR VERIFYING THE CORRECTNESS OF THE TYPE, SIZE, AND LOCATION OF ALL FITTINGS, ACCESSORIES, AND COATINGS SHOWN ON THIS DRAWING.			
 Highland Tank®			
MANUAL GREASE INTERCEPTOR			
MGI-125			
CUSTOMER: _____			
PROJECT: _____			
QUOTE NO.: _____			
ORDER: _____			
SCALE: NTS	DATE: 7/7/20	DWG. BY: MGS	DWG. NO: MGI-125
DIMENSION TOLERANCE: ± 1'			