

GENERAL SPECIFICATIONS

QUANTITY: ONE (1)
MODEL: HTM-ESP-INT-150 IF
MAXIMUM FLOW RATE: 150 GPM
TOTAL CAPACITY: 1,047 GALLONS
INTERCEPTOR STATIC CAPACITY: 418 GALLONS
MEDIA CHAMBER STATIC CAPACITY: 215 GALLONS
OIL CAPACITY: 60 GALLONS
TYPE: SINGLE WALL, UNDERGROUND
MATERIAL: 7 GA CARBON STEEL
CONTINUOUS WELD INTERIOR AND EXTERIOR SEAMS
SURFACE PREP: SSPC-SP 10 BLAST ALL SURFACES
EXT. COATING: CHEMLINE 2240
INT. COATING: CHEMLINE 4200PW - 15 MILS

NOTE: UNIT TO SHIP WITH PLASTIC PLUGS IN ALL FITTINGS NOT OTHERWISE NOTED

NOTES

STANDARD TANK MATERIAL IS COATED CARBON STEEL - STAINLESS STEEL CONSTRUCTION IS OPTIONAL

STANDARD TANK LID IS RATED FOR PEDESTRIANS ONLY - H-20 TRAFFIC RATED LIDS ARE OPTIONAL

DRAWING SHOWS STANDARD TANK HEIGHT DIMENSION FROM INLET/OUTLET FITTINGS TO FINISHED FLOOR - CUSTOMER MUST SPECIFY HEIGHT DIMENSION MODIFICATIONS NEEDED TO MEET PROJECT PLUMBING REQUIREMENTS

CUSTOMER APPROVAL

THE CUSTOMER HAS REVIEWED THIS DRAWING AND VERIFIED THE ACCURACY OF ALL INFORMATION AND DIMENSIONS.

SIGNED:

DATE:

NOTE: ALL RIGHTS RESERVED. THIS DRAWING, OR ANY PART THEREOF, MUST NOT BE REPRODUCED IN ANY FORM WITHOUT WRITTEN PERMISSION FROM HIGHLAND TANK. UNLESS OTHERWISE NOTED, HIGHLAND TANK SHALL BE RESPONSIBLE ONLY FOR ITEMS INDICATED ON THIS FABRICATION DRAWING. THE CUSTOMER IS RESPONSIBLE FOR VERIFYING THE CORRECTNESS OF THE TYPE, SIZE, AND LOCATION OF ALL FITTINGS, ACCESSORIES, AND COATINGS SHOWN ON THIS DRAWING.



Highland Tank

150 GPM ELEVATOR SUMP INTERCEPTOR

HTM-ESP-INT-150 IF

CUSTOMER:

PROJECT:

QUOTE NO.:

ORDER:

SCALE: NTS DATE: 2/14/25 DWG. BY: MGS DWG. NO.: ESP-INT-150 IF

DIMENSION TOLERANCE: ± 1"

