

NO. REQ'D: REM
MODEL: 200 R-L C
MATERIAL: 304 STAINLESS STEEL 2-B FINISH
GAUGE OR THICKNESS OF MATERIAL
10 ga. THROUGHOUT
BUILD IN ACCORDENCE WIRH U.L. 1D42
STATIC WATER CAPACITY: 311 gal
GREASE HOLDING CAPACITY: 1,885 lbs.
RETENTION TIME: 81.43 SEC.

MODEL: 200 R-L

MATERIAL: 304 STAINLESS STEEL 2-B FINISH
GAUGE OR THICKNESS OF MATERIAL

10 qa. THROUGHOUT

BUILD IN ACCORDANCE WITH U.L. 1D42

STATIC WATER CAPACITY: 311 gal

GREASE HOLDING CAPACITY: 1,885 lbs.

RETENTION TIME: 81.43 SEC.

NOTE:

CONTROL PANEL MOUNTED TO HEAD OF TANK
CUSTOMER TO ADVISE ON SUPPLY VOLTAGE & PHASE
208 / 3 / 60 UNLESS OTHERWISE NOTED
PLATFORM (NOT SHOWN) SHIPPED LOOSE

OUTLET BAFFLE

REMOVABLE
COVERS

THERMOSTAT BOX
(4 - REQ'D)

4"Ø SCH.40 INLET
PIPE (2-REQ'D)

DIFFUSION BOX
(2-REQ'D)

2"Ø HALF-COUPLING
(FTG. FOR VENT)

REMOVABLE SCREEN
BASKETS (2-REQ'D)

IMMERSION
HEATERS (4-REQ'D)

55 GALLON DRUM
FOR SKIMMED GREASE
(BY CUSTOMER)

3"Ø NPT FTG.
(FTG. FOR DRAIN)

RIGHT TO LEFT

UNIT MUST BE PLUGGED INTO
A GFI(GROUND FAULT INTERRUPT)RECEPTACLE.

GEARMOTOR- .933 FLA. 115V, 60hz
ELECTRIC HEATING ELEMENT- 115 V, 1500 W
(4) DIRECT IMMERSION ELECTRIC
HEATING ELEMENTS 16.225 FLA EA.

NOTE:

THE A.G.I. IS NOT A TRAP FOR SEWER GAS WE
SUGGEST A TRAP DOWN STREAM FROM THE A.G.I.
ALL ELECTRICAL & PLUMBING SUBJECT TO
LOCAL CODES

		<h1>Highland Tank</h1>	
<h2>REVISONS</h2>			
<p>AGI 200 RIGHT – LEFT</p> <p>SALES DRAWINGS</p>			
<p>CUSTOMER:</p>			
<p>PROJECT:</p>			
<p>QUOTE NO:</p>		<p>CHK'D BY:</p>	
<p>SCALE: 3/4"=1'</p>	<p>DATE: 8/18/09</p>	<p>DWG. BY: CNR</p>	<p>DWG. NO: 00200AGI-R-100</p>