

GENERAL SPECIFICATIONS

QUANTITY: ONE (1)  
MODEL: HTM-ESP-INT-200 IF  
MAXIMUM FLOW RATE: 200 GPM  
TOTAL CAPACITY: 1,371 GALLONS  
INTERCEPTOR STATIC CAPACITY: 532 GALLONS  
MEDIA CHAMBER STATIC CAPACITY: 285 GALLONS  
OIL CAPACITY: 68 GALLONS  
TYPE: SINGLE WALL, UNDERGROUND  
MATERIAL: 7 GA CARBON STEEL  
CONTINUOUS WELD INTERIOR AND EXTERIOR SEAMS  
SURFACE PREP: SSPC-SP 10 BLAST ALL SURFACES  
EXT. COATING: CHEMLINE 2240  
INT. COATING: CHEMLINE 4200PW - 15 MILS

NOTE: UNIT TO SHIP WITH PLASTIC PLUGS IN ALL FITTINGS NOT OTHERWISE NOTED

NOTES

STANDARD TANK MATERIAL IS COATED CARBON STEEL - STAINLESS STEEL CONSTRUCTION IS OPTIONAL

STANDARD TANK LID IS RATED FOR PEDESTRIANS ONLY - H-20 TRAFFIC RATED LIDS ARE OPTIONAL

DRAWING SHOWS STANDARD TANK HEIGHT DIMENSION FROM INLET/OUTLET FITTINGS TO FINISHED FLOOR - CUSTOMER MUST SPECIFY HEIGHT DIMENSION MODIFICATIONS NEEDED TO MEET PROJECT PLUMBING REQUIREMENTS

CUSTOMER APPROVAL

THE CUSTOMER HAS REVIEWED THIS DRAWING AND VERIFIED THE ACCURACY OF ALL INFORMATION AND DIMENSIONS.

SIGNED:

DATE:

NOTE:  
ALL RIGHTS RESERVED. THIS DRAWING, OR ANY PART THEREOF, MUST NOT BE REPRODUCED IN ANY FORM WITHOUT WRITTEN PERMISSION FROM HIGHLAND TANK. UNLESS OTHERWISE NOTED, HIGHLAND TANK SHALL BE RESPONSIBLE ONLY FOR ITEMS INDICATED ON THIS FABRICATION DRAWING. THE CUSTOMER IS RESPONSIBLE FOR VERIFYING THE CORRECTNESS OF THE TYPE, SIZE, AND LOCATION OF ALL FITTINGS, ACCESSORIES, AND COATINGS SHOWN ON THIS DRAWING.



**Highland Tank**

200 GPM ELEVATOR SUMP INTERCEPTOR

HTM-ESP-INT-200 IF

CUSTOMER:

PROJECT:

QUOTE NO.:

ORDER:

SCALE:

DATE:

DWG. BY:

DWG. NO.:

DIMENSION TOLERANCE: ± 1"

NTS

2/14/25

MGS

ESP-INT-200 IF

