

6

—53"± - BASE DF BEAMS-

(12)

<u>ا</u>دا ы 01 0 ٥l REMOVABLE ONLY IF REQUIRED FOR FABRICATION _\$_ ____ల Ľ 4″ 12" (12) -36″-

	<u>GENERAL</u> <u>SPECIFICATIONS</u> QUANTITY: ONE (1) MODEL: PGI-250-1 AR CAPACITY: 250 GALLONS TYPE: SINGLE WALL, ABOVEGROUND MATERIAL: 7 GA CARBON STEEL LAP FIT AND WELD INTERIOR AND EXTERIOR SEAMS SURFACE PREP: SSPC-SP 10 BLAST INTERIOR SURFACES SSPC-SP 6 BLAST EXTERIOR SURFACES EXT. COATING: WHITE URETHANE - 3-5 MILS INT. COATING: CHEMLINE 4200 PW (15 MILS DFT) OPERATING PRESSURE: ATMOSPHERIC GREASE HOLDING CAPACITY: 633 LBS
	 <u>PROVIDED EQUIPMENT</u> 1. 4"ø SCH 40 PIPE STUB – INLET 2. 4"ø SCH 40 PIPE STUB – OUTLET 3. 2" HC FOR VENT 4. 24"ø MANWAY WITH 18" EASY-ACCESS HATCH 5. STEEL OUTLET DOWNCOMER BAFFLE WITH OPEN TOP 6. STRIKER PLATE 7. SLUDGE BAFFLE – 7 GA 8. UNDERFLOW BAFFLE – 7 GA 9. 4"ø 45" DIFFUSION ELBOW 10. 8" x 24" REMOVABLE DIFFUSION PLATE – 7 GA 11. DIFFUSION PLATE SUPPORTS 12. (3) W4x13 BEAM RUNNER WITH (2) 7/8" HOLES AT EACH TAPERED END FOR ANCHORING 13. 2" HC – NORMAL TANK VENT 14. 3" HC FOR EMERGENCY VENT
	THIS DRAWING IS SUBJECT TO CHANGE AT THE DISCRETION OF THE MANUFACTURER. CONTACT HIGHLAND TANK FOR THE MOST UP-TO-DATE INFORMATION AND DRAWINGS OF OUR PRODUCTS. NUTE: ALL RIGHTS RESERVED. THIS DRAWING, DR ANY PART THEREDF, MUST NOT BE REPRODUCED IN ANY FORM WITHOUT WEITTEN PERMISSION FROM HIGHLAND TANK. UNLESS DTHERWISE NOTED, HIGHLAND TANK SHALL BE RESPONSIBLE DNLY FOR THEM INDICATED ON THIS FABRICATION DRAVING. THE CUSTOMER IS RESPONSIBLE FOR VERIFYING THE CORRECTNESS AND
	CATINGS SHOWN ON THIS DRAVING. WIGHTING SHOWN ON THIS DRAVING. HIGHLAND HIGHLAND PASSIVE GREASE INTERCEPTOR
	PGI-250-1 AR customer: project:
DIMENSION TOLERANCE: ± 1"	QUOTE NO.: scale: DATE: DWG. BY: DWG. NO.: NTS 10/31/23 MGS PGI-250-1 AR