NOTE: ALL RIGHTS RESERVED. THIS DRAWING MUST NOT BE REPRODUCED IN ANY FORM WITHOUT THE WRITTEN PERMISSION OF HIGHLAND TANKO, HALL BE RESPONSIBLE ONLY FOR ITEMS INDICATED ON THIS FABRICATION DRAWING UNLESS OTHERWISE NOTED, CUSTOMER IS RESPONSIBLE FOR VERTIMING OFFICENCES OF SCREEN AND COATINGS, PERMISSION OF THIS DRAWING, AND COATINGS SHOWN, ON THIS DRAWING, AND COATINGS SHOWN, ON THIS DRAWING.

TOUCH UP OF FINISHED PAINT IS REQUIRED BY INSTALLATION CONTRACTOR. TOUCH UP PAINT SHIPPED WITH TANK.

DESIGN DATA

CAPACITY - 300 GALLONS TYPE - ABOVEGROUND FIRE PROTECTION VESSEL

NO. REQ. - ___

MAX. ALLOW. WORKING PRES.- ___PSIG @ 140 °F MAX ALLOW. EXTERNAL W.P. - __PSIG @ 140 °F MIN. DESIGN METAL TEMP - __20°F @ ___PSIG

HYDROSTATIC TEST PRESSURE - ___ PSIG

CORROSION ALLOWANCE- ____

POSTWELD HEAT TREATED - ____

ADIOCRADIIV

HEADS - ___ SA516 GR 70 ASME 2:1 ELLIPTICAL SHELL - ___ SA516 GR 70

INT. FINISH - SSPC. SP10 BLAST

HIGH DRO LINER PLUS FOR NFPA 22

EXT. FINISH - GRAY SHOP PRIMER OR


OTHER TO BE SPECIFIED


CONSTRUCTION - BUTT WELD INSIDE AND OUTSIDE


ALL TANK FABRICATIONS TO BE IN ACCORDANCE WITH ASME SECTION VIII, DIVISION 1, LATEST EDITION, LATEST ADDENDA

ALL SHELL, HEAD, FITTINGS, AND MANWAYS TO BE WELDED TO BIGBEE STEEL WELD PROCEDURE PER DRAWING F11151

HIGHLAND TANK SERIAL # --







| <u>LEGEND</u> | | | | | | |
|---------------|-----------|-----------|--------|------------|--------|------------------------------------|
| MARK | SIZE | TYPE | RATING | NOZZLE | FLANGE | COMMENTS |
| Α | 12" X 16" | ELLIPT. | 300# | SA106 GR C | | w/ NEOPRENE RUBBER GASKET |
| В | | RFSO | 150# | SA106 GR B | SA105 | WITH 2" PROJECTION INSIDE THE TANK |
| С | | HALF CPLG | 3000# | SA105 | | |
| D | | HALF CPLG | 3000# | SA105 | | |

