



## GENERAL SPECIFICATIONS

QUANTITY: ONE (1)  
MODEL: AGI-300 WH RL  
MAXIMUM FLOW RATE: 300 GPM  
STATIC CAPACITY: 360.5 GALLONS  
RETENTION TIME: 72 SEC  
TYPE: SINGLE WALL, ABOVE-GROUND  
MATERIAL: 10 GA 304 STAINLESS STEEL  
BUILT IN ACCORDANCE WITH U.L. 1D42

## NOTES

STANDARD CONTROL PANEL OPERATES ON  
208V-3Ø + NEUTRAL SERVICE VOLTAGE -  
OPTIONAL PANELS AVAILABLE

GEAR MOTORS RATED AT 0.44 FLA, 115V - 60 Hz

IMMERSION HEATERS OPERATE AT 208V

ALL ELECTRICAL AND PLUMBING CONNECTIONS ARE  
SUBJECT TO LOCAL CODES

HIGHLAND TANK OFFERS A WIDE VARIETY OF OPTIONS  
AND CUSTOMIZATIONS TO ACCOMMODATE PROJECT  
CONDITIONS - CONTACT HIGHLAND TANK FOR MORE  
INFORMATION

THIS DRAWING IS SUBJECT TO CHANGE AT THE DISCRETION  
OF THE MANUFACTURER. CONTACT HIGHLAND TANK FOR  
THE MOST UP-TO-DATE INFORMATION AND DRAWINGS OF  
OUR PRODUCTS.

NOTE:  
ALL RIGHTS RESERVED. THIS DRAWING, OR ANY PART THEREOF, MUST NOT  
BE REPRODUCED IN ANY FORM WITHOUT WRITTEN PERMISSION FROM  
HIGHLAND TANK. UNLESS OTHERWISE NOTED, HIGHLAND TANK SHALL BE  
RESPONSIBLE ONLY FOR ITEMS INDICATED IN THIS FABRICATION DRAWING.  
THE CUSTOMER IS RESPONSIBLE FOR VERIFYING THE CORRECTNESS OF  
THE TYPE, SIZE, AND LOCATION OF ALL FITTINGS, ACCESSORIES, AND  
COATINGS SHOWN ON THIS DRAWING.



GreaseStopper® AUTOMATIC GREASE INTERCEPTOR  
AGI-300 WH RL

CUSTOMER:  
PROJECT:  
QUOTE NO.:  
SCALE: DATE: DWG. BY: DWG. NO.:  
NTS 1/2/19 MGS AGI-300 WH RL

DIMENSION TOLERANCE: ± 1"