

**GENERAL SPECIFICATIONS**

QUANTITY: ONE (1)  
 MODEL: MGI-300  
 MAXIMUM FLOW RATE: 300 GPM  
 STATIC CAPACITY: 580 GALLONS  
 GREASE HOLDING CAPACITY: 600 LBS  
 TYPE: SINGLE WALL, UNDERGROUND  
 MATERIAL: 7 GA CARBON STEEL  
 CONTINUOUS WELD INTERIOR AND EXTERIOR SEAMS  
 SURFACE PREP: SSPC-SP 10 BLAST ALL SURFACES  
 INT. & EXT. COATING: CHEMLINE 2240 - 15 MILS DFT

**NOTES**

STANDARD TANK MATERIAL IS COATED CARBON STEEL - STAINLESS STEEL CONSTRUCTION IS OPTIONAL

DRAWING SHOWS STANDARD TANK HEIGHT DIMENSION FROM INLET/OUTLET FITTINGS TO FINISHED FLOOR - CUSTOMER MUST SPECIFY HEIGHT DIMENSION MODIFICATIONS REQUIRED TO MEET PROJECT PLUMBING CONDITIONS

STANDARD TANK LID IS RATED FOR PEDESTRIANS ONLY - H-20 TRAFFIC RATED LIDS ARE OPTIONAL

**CUSTOMER APPROVAL**

THE CUSTOMER HAS REVIEWED THIS DRAWING AND VERIFIED THE ACCURACY OF ALL INFORMATION AND DIMENSIONS.

SIGNED: \_\_\_\_\_

DATE: \_\_\_\_\_

**NOTE:**  
 ALL RIGHTS RESERVED. THIS DRAWING, OR ANY PART THEREOF, MUST NOT BE REPRODUCED IN ANY FORM WITHOUT WRITTEN PERMISSION FROM HIGHLAND TANK. UNLESS OTHERWISE NOTED, HIGHLAND TANK SHALL BE RESPONSIBLE ONLY FOR ITEMS INDICATED ON THIS FABRICATION DRAWING. THE CUSTOMER IS RESPONSIBLE FOR VERIFYING THE CORRECTNESS OF THE TYPE, SIZE, AND LOCATION OF ALL FITTINGS, ACCESSORIES, AND COATINGS SHOWN ON THIS DRAWING.



**MANUAL GREASE INTERCEPTOR  
 MGI-300**

CUSTOMER: \_\_\_\_\_

PROJECT: \_\_\_\_\_

QUOTE NO.: \_\_\_\_\_

ORDER: \_\_\_\_\_

SCALE: \_\_\_\_\_ DATE: 7/7/20 DWG. BY: MGS DWG. NO.: MGI-300

DIMENSION TOLERANCE: ± 1'

