

NUTTE:


REGISTS RESSERVED THIS DRAWING, DR ANY PART THEREOF, MUST NOT

RE REPORTINGED IN ANY FIRM WITHOUT WRITTEN REPORTS TON FROM

HOGE-AND TAKE, MULESS DITTENVISE NOTICE, HIGH-AND TAKE SHALL BE

RESPONSIBLE DNLY FOR TENN INDICATED ON THIS FABRICATION DRAWING.

THE LOUSTINGE IS RESPONSIBLE FOR VERTIFIEND THE CONTROLLED TO THE THE CASTONER TO THE THE CASTONER AND CONTROL OF THE THE STATE AND THE STATE OF THE STAT



## GENERAL SPECIFICATIONS

MODEL: PGI-300 AC NOMINAL CAPACITY: 360 GALLONS STATIC WATER CAPACITY: 303.3 GALLONS TYPE: SINGLE WALL, ABOVEGROUND MATERIAL: MILD CARBON STEEL GAUGE OF SHELL: 7 GA GAUGE OF HEADS: 7 GA

LAP FIT AND WELD INTERIOR AND EXTERIOR SEAMS SURFACE PREP: SSPC-SP 10 BLAST INTERIOR SURFACES SSPC-SP 6 BLAST EXTERIOR SURFACES

COATING, EXTERIOR: WHITE URETHANE - 3-5 MILS COATING, INTERIOR: POLYURETHANE - 15 MILS OPERATING PRESSURE: ATMOSPHERIC APPROXIMATE DRY WEIGHT: 1,200 LBS

## PROVIDED EQUIPMENT

- 1. 4"ø SCH 40 PIPE STUB 2. UNDERFLOW BAFFLE - 7 GA
- 3. 2" NPT FTG FOR VENT
- 4. 24"ø MANWAY W/ EASY-ACCESS HATCH
- 5. STEEL OUTLET DOWNCOMER BAFFLE W/ OPEN TOP FOR EFFLUENT SAMPLING
- 6. 1/4" STRIKER PLATE (AT ALL MANWAYS)
- 7. SLUDGE BAFFLE 7 GA
- 8. VELOCITY DIFFUSION BREAKER
- 9. 4"ø 45° DIFFUSION ELBOW
- 10. 2" NPT NORMAL TANK VENT
- 11. REMOVABLE DIFFUSION PLATE -1/4" 12. 8" x 8" WEAR PLATE -1/4"
- 13. 6" HIGH STEEL SADDLE SEAL WELD TO TANK
- 14. 4" NPT FOR EMERGENCY VENT

## CUSTOMER APPROVAL

THE CUSTOMER HAS REVIEWED THIS DRAWING AND VERIFIED THE ACCURACY OF ALL INFORMATION AND DIMENSIONS.

SIGNED:

DATE:



REVISIONS

PASSIVE GREASE INTERCEPTOR 300 GALLON

CUSTOMER:

PROJECT:

QUOTE NO:

CHK'D BY:

SCALE: DATE: DWG BY
DIMENSION TOLERANCE: ± 1" N T S 11/2/12 MGS

PGI-300