

	<u>GENERAL</u> <u>SPECIFICATIONS</u> QUANTITY: ONE (1) MODEL: MOI-400 MAXIMUM FLOW RATE: 400 GPM STATIC CAPACITY: 637 GALLONS TYPE: SINGLE WALL, UNDERGROUND MATERIAL: 10 GA CARBON STEEL CONTINUOUS WELD INTERIOR AND EXTERIOR SEAMS SURFACE PREP: SSPC-SP 10 BLAST ALL SURFACES INT. & EXT. COATING: CHEMLINE 2240 – 15 MILS DFT <u>NOTES</u> STANDARD TANK MATERIAL IS COATED CARBON STEEL – STAINLESS STEEL CONSTRUCTION IS OPTIONAL DRAWING SHOWS STANDARD TANK HEIGHT DIMENSION FROM INLET/OUTLET FITTINGS TO FINISHED FLOOR – CUSTOMER MUST SPECIFY HEIGHT DIMENSION MODIFICATIONS REQUIRED TO MEET PROJECT PLUMBING CONDITIONS STANDARD TANK LID IS RATED FOR PEDESTRIANS ONLY – H-20 TRAFFIC RATED LIDS ARE OPTIONAL INTEGRAL OIL STORAGE CHAMBERS AND HIGH LEVEL ALARMS ARE AVAILABLE AS OPTIONS
- 2" FNPT VENT	
D	
	NDTE: ALL RIGHTS RESERVED. THIS DRAWING, DR ANY PART THEREDF, MUST NOT BE REPRODUCED IN ANY FORM WITHOUT WRITTEN PERMISSION FROM HIGHLAND TANK, UNLESS OTHERVISE NOTED, HIGHLAND TANK SHALL BE RESPONSIBLE DNLY FOR ITEMS INDICATED DN THIS FABRICATION DRAWING. THE CUSTOMER IS RESPONSIBLE FOR VERIFYING THE CORRECTNESS OF COATINGS SHOWN ON THIS DRAWING.
	MANUAL OIL INTERCEPTOR MOI-400 customer: project:
DIMENSION TOLERANCE: ± 1"	QUOTE NO.: SCALE: DATE: DVG. BY: DVG. NG: NTS 7/7/20 MGS MG. DVG. NG: - 400