

	<u>GENERAL SPECIFICATIONS</u> QUANTITY: ONE (1) MODEL: MOI-400 SO MAXIMUM FLOW RATE: 400 GPM STATIC CAPACITY: 613 GALLONS OIL STORAGE CAPACITY: 475 GALLONS TYPE: SINGLE WALL, UNDERGROUND MATERIAL: 7 GA CARBON STEEL CONTINUOUS WELD INTERIOR AND EXTERIOR SEAMS SURFACE PREP: SSPC-SP 10 BLAST ALL SURFACES INT. & EXT. COATING: CHEMLINE 2240 – 15 MILS DFT
	<u>NOTES</u> STANDARD TANK MATERIAL IS COATED CARBON STEEL – STAINLESS STEEL CONSTRUCTION IS OPTIONAL DRAWING SHOWS STANDARD TANK HEIGHT DIMENSION FROM INLET/OUTLET FITTINGS TO FINISHED FLOOR – <u>CUSTOMER</u> <u>MUST SPECIFY HEIGHT DIMENSION MODIFICATIONS REQUIRED TO</u> <u>MEET PROJECT PLUMBING CONDITIONS</u>
	STANDARD TANK LID IS RATED FOR PEDESTRIANS ONLY – H–20 TRAFFIC RATED LIDS ARE OPTIONAL
- 2" FNPT VENT	CUSTOMER APPROVAL
6" 14" TO INVERT	DRAWING AND VERIFIED THE ACCURACY OF ALL INFORMATION AND DIMENSIONS. SIGNED: DATE:
18″ — — 🕖	NDTE: ALL RIGHTS RESERVED. THIS DRAVING, DR ANY PART THEREDF, MUST NDT BE REPRODUCED IN ANY FORM VITHOUT WRITTEN PERMISSION FROM HIGHLAND TANK, UNLESS OTHERVISE NOTED, HIGHLAND TANK SHALL BE RESPONSIBLE DNLY FOR ITEMS INDICATED ON THIS FABRICATION DRAVING. THE CUSTOMER IS RESPONSIBLE FOR VERIFYING THE CUBRECTNESS OF THE TYPE, SIZE, AND LOCATION OF ALL FITTINGS, ACCESSORIES, AND COATINGS SHOWN ON THIS DRAVING.
	MANUAL OIL INTERCEPTOR MOI-400 SO
	CUSTOMER: PROJECT: QUOTE NO.: SCALE: NTS 2/14/25 MGS MOI-400 SO