

NOTE: ALL RIGHTS RESERVED. THIS
DRAWING MUST NOT BE REPRODUCED IN
ANY FORM WITHOUT THE WRITTEN
PERMISSION OF HIGHLAND TANK®.
HIGHLAND TANK® SHALL BE RESPONSIBLE
ONLY FOR ITEMS INDICATED ON THIS
FABRICATION DRAWING UNLESS OTHERWISE
NOTED. CUSTOMER IS RESPONSIBLE FOR
VERIFYING CORRECTNESS OF SIZE AND
LOCATION OF FIITINGS, ACCESSORIES, AND
COATINGS SHOWN ON THIS DRAWING.

TOUCH UP OF FINISHED PAINT IS REQUIRED BY INSTALLATION CONTRACTOR. TOUCH UP PAINT SHIPPED WITH TANK.

SHIP LOOSE


- (1) 4" MALE THREADED EMERGENCY VENTS
- (1) 6" FLANGED EMERGENCY VENTS
- (1) HIGH-LINK LEVEL SHIELD MODEL# LS_XEXD_1500 59" INCLUDESLONG & 2" X \(\frac{3}{4}" \) BUSHING WITH LS_LINK_GPRS COMMUNICATION BOX.






NOTES:

STRIKER PLATES ARE NOT SUPPLIED ON FIREGUARDS® UNLESS SPECIFIED



HIGH-LINK LEVEL SHIELD DETAIL



COMMUNICATION BOX DETAIL

DESIGN DATA

CAPACITY: 500 GALLON

TYPE: FIREGUARD® RECTANGULAR

FIREGUARD® IS A TRADEMARK OF THE STEEL TANK

INSTITUTE

NO. REQ. - 1

OPERATING PRESSURE - ATMOSPHERIC

SPECIFIC GRAVITY = 1.0

TANK MATERIAL - MILD CARBON STEEL

THICKNESS - INNER - 7 GAUGE

THICKNESS — OUTER — 7 GAUGE

MIN. GAUGE OR THICKNESS (PER U.L. 2085)

CONSTRUCTION — INNER — LAP WELD OUTSIDE ONLY CONSTRUCTION — OUTER — LAP WELD OUTSIDE ONLY

TANK TEST - INNER - 1.5 TO 3 PSIG OUTER - 1.5 TO 3 PSIG


INT. FINISH - NONE

EXT. FINISH - SP-6 BLAST, FINISH PAINT WHITE

LABEL- UL 2085 AND FIREGUARD® PER sti

LEGEND

- A 2" FEMALE FIREGUARD COUPLING
- B 4" female fireguard coupling
- C 4" FEMALE FIREGUARD COUPLING FOR PRIMARY EMERGENCY VENT USE ONLY
- D 6" FFSO 150# FLANGE THROUGH OUTER SHELL ONLY, MARK WITH SPECIAL WARNING LABEL INTERSTITIAL EMERGENCY VENT USE ONLY
- 2" FITTING THROUGH OUTER SHELL ONLY WITH CAST IRON PLUG FOR MFG USE ONLY
- 2" INTERSTITIAL MONITOR PIPE MALE NPT





UNLESS NOTED, TOLERANCES ARE +/- 1"

500 GAL REC. FIREGUARD®

PATENT: 5,695,089 PATENT: 5,809,650

CUSTOMER:

PROJECT:

QUOTE NO:

CHK'D BY:

SCALE: DATE: DWG. BY: 1/2"=1'-0" XX/XX/XX XXX

00500FGREC