



NOTES

STANDARD CONTROL PANEL OPERATES ON 208V-3Ø + NEUTRAL
SERVICE VOLTAGE - OPTIONAL PANELS AVAILABLE

GEAR MOTORS RATED AT 0.44 FLA, 115V - 60 Hz

IMMERSION HEATERS OPERATE AT 208V

ALL ELECTRICAL AND PLUMBING CONNECTIONS ARE SUBJECT TO LOCAL CODES

HIGHLAND TANK OFFERS A WIDE VARIETY OF OPTIONS AND CUSTOMIZATIONS TO ACCOMMODATE PROJECT CONDITIONS - CONTACT HIGHLAND TANK FOR MORE INFORMATION

GENERAL SPECIFICATIONS

QUANTITY: ONE (1)
MODEL: AGI-500 WH RL
MAXIMUM FLOW RATE: 500 GPM
STATIC CAPACITY: 552 GALLONS
RETENTION TIME: 66.3 SEC
TYPE: SINGLE WALL, ABOVE-GROUND
MATERIAL: 10 GA 304 STAINLESS STEEL
BUILT IN ACCORDANCE WITH U.L. 1D42

THIS DRAWING IS SUBJECT TO CHANGE AT THE DISCRETION OF THE MANUFACTURER. CONTACT HIGHLAND TANK FOR THE MOST UP-TO-DATE INFORMATION AND DRAWINGS OF OUR PRODUCTS.



Highland Tank®

GreaseStopper® AUTOMATIC GREASE INTERCEPTOR

AGI-500 WH RL

CUSTOMER:

PROJECT:

QUOTE NO.:

ORDER:

SCALE: DATE: DWG. BY: DWG. NO.:

1/2/19 MGS AGI-500 WH RL

DIMENSION TOLERANCE: ± 1"

NOTE:
ALL RIGHTS RESERVED. THIS DRAWING, OR ANY PART THEREOF, MUST NOT BE REPRODUCED IN ANY FORM WITHOUT WRITTEN PERMISSION FROM HIGHLAND TANK. UNLESS OTHERWISE NOTED, HIGHLAND TANK SHALL BE RESPONSIBLE ONLY FOR ITEMS INDICATED ON THIS FABRICATION DRAWING. THE CUSTOMER IS RESPONSIBLE FOR VERIFYING THE CORRECTNESS OF THE TYPE, SIZE, AND LOCATION OF ALL FITTINGS, ACCESSORIES, AND COATINGS SHOWN ON THIS DRAWING.