





GENERAL SPECIFICATIONS

QUANTITY: DNE (1) MDDEL: MGI-500N MAXIMUM FLOW RATE: 500 GPM STATIC WATER CAPACITY: 500 GAL GREASE HOLDING CAPACITY: 1,000 LBS MATERIAL: 7 GA CARBON STEEL SINGLE-WALL CONSTRUCTION SURFACE PREP: SSPC-SP 10 BLAST ALL

INTERIOR AND EXTERIOR COATING: CHEMTHANE 2240 POLYURETHANE - 15 MILS DF1

SURFACES

NOTES:

STANDARD TANK MATERIAL IS COATED CARBON STEEL - STAINLESS STEEL CONSTRUCTION IS AVAILABLE.

DRAWING SHOWS STANDARD TANK HEIGHT. CUSTOMER MUST SPECIFY ACTUAL HEIGHT DIMENSION REQUIRED.

ALL PLUMBING CONNECTIONS MUST COMPLY WITH LOCAL CODES AND REGULATIONS.

CUSTOMER APPROVAL

THE CUSTOMER HAS REVIEWED THIS DRAWING AND VERIFIED THE ACCURACY OF ALL INFORMATION AND DIMENSIONS.

SIGNED:

DATE:

NOTE:
ALL RIGHTS RESERVED. THIS DRAVING, DR ANY PART THEREOF, MUST NOT
BE REPRODUCED IN ANY FORM WITHOUT WRITTEN PERMISSION FROM
HIGHLAND TANK UNLESS OTHERWISE NOTED, HIGHLAND TANK SHALL BE
RESPONSIBLE DNLY FOR ITEMS INDICATED ON THIS FABRICATION DRAWING.
THE CUSTOMER IS RESPONSIBLE FOR VERIFYING THE CORRECTNESS OF
THE TYPE, SIZE, AND LICCATION OF ALL FITTINGS, ACCESSORIES, AND
CDATINGS SHOWN ON THIS DRAWING.

THIS DRAWING IS SUBJECT TO CHANGE AT THE DISCRETION OF THE MANUFACTURER. CONTACT HIGHLAND TANK FOR THE MOST UP-TO-DATE INFORMATION AND DRAWINGS OF OUR PRODUCTS.



MANUAL GREASE INTERCEPTOR MGI-500N

CUSTOMER:

PROJECT:

DIMENSION TOLERANCE: ± 1' NTS |2/12/18 MGS | MGI - 500N