



GENERAL SPECIFICATIONS

QUANTITY: ONE (1)
 MODEL: MGI-500N
 MATERIAL: 7 GA CARBON STEEL
 SINGLE-WALL CONSTRUCTION
 SURFACE PREP: SSPC-SP 10 BLAST ALL SURFACES
 INT. & EXT. COATING: POLYURETHANE
 MAXIMUM FLOW RATE: 500 GPM
 STATIC WATER CAPACITY: 506 GAL
 GREASE HOLDING CAPACITY: 1,000 LBS
 APPROXIMATE DRY WEIGHT: 1,450 LBS

NOTES:

STANDARD TANK MATERIAL IS COATED
 CARBON STEEL - STAINLESS STEEL
 CONSTRUCTION IS AVAILABLE.

DRAWING SHOWS STANDARD TANK HEIGHT.
 CUSTOMER MUST SPECIFY ACTUAL
 HEIGHT DIMENSION REQUIRED.

ALL PLUMBING CONNECTIONS MUST COMPLY
 WITH LOCAL CODES AND REGULATIONS.

CUSTOMER APPROVAL

THE CUSTOMER HAS REVIEWED THIS
 DRAWING AND VERIFIED THE ACCURACY OF
 ALL INFORMATION AND DIMENSIONS.

SIGNED: _____

DATE: _____



REVISIONS



Highland Tank®

MANUAL GREASE INTERCEPTOR
 MGI-500N

CUSTOMER: _____

PROJECT: _____

QUOTE NO: _____

SCALE: _____ DATE: 10/19/12

DWG BY: MGS

CHK'D BY: _____

DWG NO: MGI-500N

DIMENSION TOLERANCE: ± 1"

NOTE:
 ALL RIGHTS RESERVED. THIS DRAWING, OR ANY PART THEREOF, MUST NOT
 BE REPRODUCED IN ANY FORM WITHOUT WRITTEN PERMISSION FROM
 HIGHLAND TANK. UNLESS OTHERWISE NOTED, HIGHLAND TANK SHALL BE
 RESPONSIBLE ONLY FOR ITEMS INDICATED ON THIS FABRICATION DRAWING.
 THE CUSTOMER IS RESPONSIBLE FOR VERIFYING THE CORRECTNESS OF
 THE TYPE, SIZE, AND LOCATION OF ALL FITTINGS, ACCESSORIES, AND
 COATINGS SHOWN ON THIS DRAWING.