



**NOTES**

STANDARD CONTROL PANEL OPERATES ON 208V-3Ø + NEUTRAL  
SERVICE VOLTAGE – OPTIONAL PANELS AVAILABLE

GEAR MOTORS RATED AT 0.44 FLA, 115V – 60 Hz

IMMERSION HEATERS OPERATE AT 208V

ALL ELECTRICAL AND PLUMBING CONNECTIONS ARE SUBJECT TO LOCAL CODES

HIGHLAND TANK OFFERS A WIDE VARIETY OF OPTIONS AND CUSTOMIZATIONS TO ACCOMMODATE PROJECT CONDITIONS – CONTACT HIGHLAND TANK FOR MORE INFORMATION

**GENERAL SPECIFICATIONS**

QUANTITY: ONE (1)  
MODEL: AGI-800 WH LR  
MAXIMUM FLOW RATE: 800 GPM  
STATIC CAPACITY: 1,088 GALLONS  
RETENTION TIME: 81.6 SEC  
TYPE: SINGLE WALL, ABOVE-GROUND  
MATERIAL: 10 GA 304 STAINLESS STEEL  
BUILT IN ACCORDANCE WITH U.L. 1D42

THIS DRAWING IS SUBJECT TO CHANGE AT THE DISCRETION OF THE MANUFACTURER. CONTACT HIGHLAND TANK FOR THE MOST UP-TO-DATE INFORMATION AND DRAWINGS OF OUR PRODUCTS.

**Highland Tank®**

GreaseStopper® AUTOMATIC GREASE INTERCEPTOR

AGI-800 WH LR

CUSTOMER:  
PROJECT:

QUOTE NO.:  
SCALE: DATE: DWG. BY: DWG. NO.:  
NTS 1/2/19 MGS

ORDER:  
AGI-800 WH LR

DIMENSION TOLERANCE: ± 1"