

NOTE: ALL RIGHTS RESERVED. THIS DRAWING MUST NOT BE REPRODUCED IN ANY FORM WITHOUT THE WRITTEN PERMISSION OF HIGHLAND TANK® FROM THE RESPONSIBLE ONLY FOR ITEMS INDICATED ON THIS FABRICATION DAY THE RESPONSIBLE FOR VERIFYING CORRECTNESS OF SIZE AND LOCATION OF FITTINGS, ACCESSORIES, AND COATINGS SHOWN ON THIS DRAWING. TOUCH OF THE RESPONSIBLE FOR VERIFYING CORRECTNESS OF BRAWING. TOUCH UP DEFTINISHED PAINT IS REQUIRED BY INSTALLATION CONTRACTOR. TOUCH UP PAINT SHIPPED WITH TANK.

SHIPPING LUGS AS NEEDED





DESIGN DATA		
CAPACITY - 3,000 GALLONS	Α	FLANC
TYPE - POTABLE WATER TANK (PWT) NO. REO	В	FLANC
OPERATING PRESSURE — ATMOSPHERIC SPECIFIC GRAVITY = 1.0	С	24" > THICK
TANK MATERIAL — MILD CARBON STEEL	D	4" FN
THICKNESS — HEADS: 7 GA THICKNESS — SHELL: 7 GA	E	STD H ASSEM
CONSTRUCTION - LAP WELD INSIDE AND OUTSIDE	_	AND S
TANK TEST - 5 PSIG	F	нтм з
INT. FINISH — SP10 BLAST HighDRO®—LINER PLUS FOR NSF 61 APPLICATIONS	G	FLANG SHOW
EXT. FINISH — SSPC SP6 BLAST, WHITE URETHANE PAINT LABEL — NONE	Н	FB-3'
I		

LEGEND				
Α	FLANGE - SUPPLY			
В	FLANGE - VENT			
С	24" X ¼" PLATE TIGHT BOLT MANWAY WITH ½" THICK NEO-CORK GASKET			
D	4" FNPT CONNECTION			
E	STD HTM EXTERNAL LADDER & PLATFORM ASSEMBLY — PAINTED SAFETY YELLOW AND SHIPPED LOOSE FOR INSTALLATION ON SITE BY OTHERS			
F	HTM STD INTERNAL LADDER			
G	FLANGE WITH INTERNAL 90° ELBOW SHOWN — OVERFLOW			
Н	FB-3"x 1/4"x3" WITH 5/8"Ø HOLE ON CL (GROUNDING LUG)			

30"			
E			
	4'-10"	4'-6" 18" 15"	
	C	B D D [-]	G 18 ¹ / ₂ "
	F		26 <u>1</u> "
	7'-8"	7'-8"	
-	18'-	-0"	

