





NDTE: ALL RIGHTS RESERVED. THIS DRAWING, DR ANY PART THEREDF, MUST NDT BE REPRODUCED IN ANY FORM WITHOUT WRITTEN PERMISSION FROM HIGHLAND TANK, UNLESS OTHERVISE NOTED, HIGHLAND TANK SHALL BE RESPONSIBLE DNLY FOR ITEMS INDICATED ON THIS FABRICATION DRAWING. THE CUSTOMER IS RESPONSIBLE FOR VERIFYING THE CORRECTNESS OF THE TYPE, SIZE, AND LOCATION OF ALL FITTINGS, ACCESSORIES, AND COATINGS SHOWN ON THIS DRAWING.

0 0	<u>GENERAL SPECIFICATIONS</u> QUANTITY: ONE (1) MODEL: PGI-3500-3 AR CAPACITY: 3,500 GALLONS TYPE: SINGLE WALL, ABOVEGROUND MATERIAL: 7 GA CARBON STEEL WITH 1/4" BOTTOM LAP FIT AND WELD INTERIOR AND EXTERIOR SEAMS SURFACE PREP: SSPC-SP 10 BLAST INTERIOR SURFACES SSPC-SP 6 BLAST EXTERIOR SURFACES EXT. COATING: WHITE URETHANE – 3–5 MILS INT. COATING: CHEMLINE 4200 PW (15 MILS DFT) OPERATING PRESSURE: ATMOSPHERIC
	<ul> <li>PROVIDED EQUIPMENT</li> <li>1. 4"Ø SCH 40 PIPE STUB – INLET</li> <li>2. 4"Ø SCH 40 PIPE STUB – OUTLET</li> <li>3. DIFFUSION PLATE – 7 GA</li> <li>4. 16" x 16" WEAR PLATE – 1/4"</li> <li>5. GREASE DAM – 7 GA</li> <li>6. STRIKER PLATE</li> <li>7. SLUDGE BAFFLE – 7 GA</li> <li>8. UNDERFLOW BAFFLE – 7 GA</li> <li>9. 4"Ø 45° DIFFUSION ELBOW</li> <li>10. 2"Ø OPENING FOR AIR CIRCULATION</li> <li>11. STEEL OUTLET DOWNCOMER BAFFLE WITH OPEN TOP</li> <li>12. 2" HC – VENT</li> <li>13. 24"Ø MANWAY WITH 18" EASY-ACCESS HATCH</li> <li>14. (4) W6x15 BEAM RUNNER WITH (2) 1–1/8" HOLES AT EACH TAPERED END FOR ANCHORING</li> <li>15. 2" HC – NORMAL TANK VENT</li> <li>16. 6"Ø-150# FFSO FLANGE FOR EMERGENCY VENT</li> </ul>
12 2 10' 10' 56''± TD CL DF DUTLET	
	THIS DRAWING IS SUBJECT TO CHANGE AT THE DISCRETION OF THE MANUFACTURER. CONTACT HIGHLAND TANK FOR THE MOST UP-TO-DATE INFORMATION AND DRAWINGS OF OUR PRODUCTS.
<b>→</b>	passive grease interceptor PGI-3500-3 AR
DIMENSION TOLERANCE: ± 1"	CUSTOMER: PROJECT: QUOTE NO.: SCALE: NTS 10/31/23 MGS PGI-3500-3 AR
UMENSION IULERANUE: I I	NTS 10/31/23 MGS PGI-3500-3 AR