


NOTE: ALL RIGHTS RESERVED. THIS DRAWING MUST NOT BE REPRODUCED IN ANY FORM WITHOUT THE WRITTEN PERMISSION OF HIGHLAND TANK® HIGHLAND TANK® HIGHLAND TANK® SHALL BE RESPONSIBLE ONLY FOR ITEMS INDICATED ON THIS FABRICATION DRAWING UNLESS OTHERWISE NOTED. CUSTOMER IS RESPONSIBLE FOR VERIFYING CORRECTIVESS OF SIZE AND LOCATION OF FITTINGS, ACCESSORIES, AND COATINGS SHOWN ON THIS DRAWING.

TOUCH UP OF FINISHED PAINT IS
REQUIRED BY INSTALLATION
CONTRACTOR. TOUCH UP PAINT SHIPPED
WITH TANK.

SHIPPING LUGS AS NEEDED







DESIGN DATA	LEGEND
CAPACITY - 4,000 GALLONS	A FLANGE - SUPPLY
TYPE – POTABLE WATER TANK (PWT)	
NO. REQ	B FLANGE - VENT
OPERATING PRESSURE — ATMOSPHERIC SPECIFIC GRAVITY = 1.0	C 24" X 1 PLATE TIGHT BOLT MANWAY WITH 1 THICK NEO-CORK GASKET
TANK MATERIAL – MILD CARBON STEEL THICKNESS – HEADS: 5/16"	D 4" FNPT CONNECTION
THICKNESS - SHELL: 1/4"	STD HTM EXTERNAL LADDER & PLATFORM ASSEMBLY - PAINTED SAFETY YELLOW
CONSTRUCTION — LAP WELD INSIDE AND OUTSIDE	E ASSEMBLY — PAINTED SAFETY YELLOW AND SHIPPED LOOSE FOR INSTALLATION ON SITE BY OTHERS
TANK TEST – 5 PSIG	F HTM STD INTERNAL LADDER
INT. FINISH - SP10 BLAST HighDRO®-LINER	
PLUS FOR NSF 61 APPLICATIONS	G FLANGE WITH INTERNAL 90° ELBOW
EXT. FINISH - SSPC SP6 BLAST, WHITE URETHANE	SHOWN - OVERFLOW
PAINT	H FB-3"x 1/4"x3" WITH 5/8"Ø HOLE ON CL
LABEL – NONE	(GROUNDING LUG)

