GENERAL SPECIFICATIONS

NO. REQ'D:(1)

CAPACITY: 5000 GALLON

TYPE: HT. HIGHGUARD, SINGLE WALL, "G" SERIES

MATERIAL: MILD CARBON STEEL

FLOW RATE: 500 GPM

GAUGE:

SHELL- 7 GA. HEADS- 7 GA.

SURFACE PREP: SP-6 BLAST ALL EXTERIOR SURFACES

COATING: EXTERIOR-INTERIOR-

MATERIAL HIGHGUARD THICKNESS 75 MILS


NONE

CONSTRUCTION : LAP FIT & WELD ALL EXTERIOR SEAMS

OPERATING PRESSURE: ATMOSPHERIC

(18 (15)(18) (16

PLAN



FND VIFW

ALL RIGHTS RESERVED. THIS DRAWING OR ANY PART THEREOF MUST NOT BE REPRODUCED IN ANY FORM WITHOUT THE WRITTEN PERMISSION OF HIGHLAND TANK.

HIGHLAND TANK SHALL BE RESPONSIBLE ONLY FOR ITEMS INDICATED ON THIS FABRICATION DRAWING UNLESS OTHERWISE NOTED. CUSTOMER IS RESPONSIBLE FOR VERIFYING CORRECTNESS OF SIZE / LOCATION OF FITTINGS, ACCESSORIES & COATINGS SHOWN ON THIS DRAWING

- 1. POLYURETHANE HIGHGUARD TANK IS NOT APPROVED FOR THE STORAGE OF HEATED PRODUCTS
- 2. ALL VENT PIPING BY INSTALLER
- 3. 15000 VOLT SPARK TEST PROVIDED AT FACTORY

PROVIDED EQUIPMENT 1. 150# R.F.S.O. FLANGE W/ 2" NPT FOR VENT 2. 7 GÄ. BULKHEAD

3. VELOCITY HEAD DIFFUSION BAFFLE

4. WEAR PLATE

5. SEDIMENT CHAMBER

6. UNDERFLOW BAFFLE

7. SLUDGE BAFFLE

8. STRIKER PLATES

9. PARALLEL CORRUGATED PLATE COALESCER

10. OIL/WATER SEPARATOR CHAMBER

11. SLUDGE CHAMBER

12. OUTLET DOWNCOMER

13. 24"Ø MANWAY WITH BOLT-ON EXTENSION SHIPPED LOOSE

14. 4"ø FTG. FOR OIL PUMP-OUT W/ INTERNAL PIPE INSTALLED AND RISER PIPE SHIPPED LOOSE

15. 2"Ø FTG. FOR LEVEL SENSOR W/ RISER PIPE SHIPPED LOOSE

16. LIFTING LUG

17. 2"ø FTG. FOR VENT TYP. BOTH MANWAYS

18. 4"ø FTG. FOR GAUGE WITH PLUG TYP. BOTH MANWAYS

