

3	GENERAL SPECIFICATIONS QUANTITY: ONE (1) MODEL: PGI-5000 FL STATIC CAPACITY: 5,000 GALLONS TYPE: SINGLE WALL, HIGHGUARD, UNDERGROUND MATERIAL: 1/4" CARBON STEEL SHELL, 5/16" HEADS MATERIAL BASED ON 120" MAXIMUM BURIAL DEPTH LAP FIT AND WELD INTERIOR AND EXTERIOR SEAMS TANK TEST: 3-5 PSI AIR TEST SURFACE PREP: SSPC-SP 10 BLAST INTERIOR SURFACES SSPC-SP 6 BLAST EXTERIOR SURFACES EXT. COATING: HIGHGUARD POLYURETHANE – 75 MILS INT. COATING: CHEMTHANE 4200 PW (15 MILS DFT) OPERATING PRESSURE: ATMOSPHERIC <u>NOTE</u> : OPTIONAL 2" VENTS ON MANWAY RISERS AT THE DISCRETION OF THE OWNER PROVIDED EQUIPMENT
	<ol> <li>6"Ø SCH 40 PIPE STUB - INLET</li> <li>6"Ø SCH 40 PIPE STUB - OUTLET</li> <li>2" HC FOR VENT</li> <li>24"Ø MANWAY FOR STACKABLE RISER</li> <li>STEEL OUTLET DOWNCOMER BAFFLE WITH OPEN TOP</li> <li>STRIKER PLATE</li> <li>6"Ø SCH 40 STEEL TRANSFER TEE</li> <li>BOLT-ON INLET DIFFUSION BAFFLE - 7 GA</li> <li>6"Ø 45' DIFFUSION ELBOW</li> <li>FULL BULKHEAD - 1/4"</li> <li>2" OPENING FOR AIR CIRCULATION</li> <li>36"Ø GRADE-LEVEL MANWAY - SHIPPED LOOSE</li> <li>24"Ø × 12" STACKABLE RISER - ALL STACKABLE RISER COMPONENTS ARE PRE-ASSEMBLED AND COMPLETE MANWAY RISER IS SHIPPED LOOSE</li> <li>(2) 24"Ø × 6" STACKABLE RISER</li> <li>STACKABLE RISER ADAPTER RING &amp; GASKET</li> <li>STACKABLE RISER SAFETY SCREEN</li> <li>(4) CDA-15 CONCRETE DEADMAN</li> <li>(4) POLYESTER HOLD-DOWN STRAPS</li> </ol>
67"± GRADE TO DUTLET INVERT	THIS DRAWING IS SUBJECT TO CHANGE AT THE DISCRETION OF THE MANUFACTURER. CONTACT HIGHLAND TANK FOR THE MOST UP-TO-DATE INFORMATION AND DRAWINGS OF OUR PRODUCTS.
-	CUSTOMER: PROJECT:
DIMENSION TOLERANCE: ± 1"	QUOTE NO.: SCALE: DATE: NTS 3/23/16 MGS PGI-5000 FL