





SECTION VIEW

NULLE:
ALL RIGHTS RESERVED. THIS DRAWING, DR ANY PART THEREOF, MUST NOT
BE REPRODUCED IN ANY FORM WITHOUT WRITTEN PERMISSION FROM
HIGHLAND TANK UNLESS DTHERWISE NOTED, HIGHLAND TANK SHALL BE
RESPONSIBLE DNLY FOR ITEMS INDICATED ON THIS FABRICATION DRAWING.
THE CUSTOMER IS RESPONSIBLE FOR VERIFYING THE CORRECTNESS OF
THE TYPE, SIZE, AND LOCATION OF ALL FITTINGS, ACCESSORIES, AND
CDATINGS SHOWN ON THIS DRAWING.

108"±-

GENERAL SPECIFICATIONS

QUANTITY: ONE (1)

MODEL: PGI-5000-3

OPERATING CAPACITY: 5,021 GALLONS
TYPE: SINGLE WALL, HIGHGUARD, UNDERGROUND

MATERIAL: 1/4" CARBON STEEL

MATERIAL BASED ON 60" MAXIMUM BURIAL DEPTH

LAP FIT AND WELD INTERIOR AND EXTERIOR SEAMS

TANK TEST: 3-5 PSI AIR TEST SURFACE PREP: SSPC-SP 10 BLAST INTERIOR SURFACES

SSPC-SP 6 BLAST EXTERIOR SURFACES

EXT. COATING: HIGHGUARD POLYURETHANE - 75 MILS INT. COATING: CHEMLINE 4200 PW (15 MILS DFT)

OPERATING PRESSURE: ATMOSPHERIC

NOTE: OPTIONAL 2" VENTS ON MANWAY RISERS AT THE DISCRETION OF THE OWNER

PROVIDED EQUIPMENT

- 1. 6"ø SCH 40 PIPE STUB INLET
- 2. 6"ø SCH 40 PIPE STUB OUTLET
- 3. 2" HC VENT
- 4. 24"ø MANWAY FOR STACKABLE RISER
- 5. 8" SQUARE STEEL OUTLET BAFFLE WITH OPEN TOP
- STRIKER PLATE
- 7. SLUDGE BAFFLE 1/4"
- 8. UNDERFLOW BAFFLE 1/4"
- 9. 6"ø 45" DIFFUSION ELBOW
- 10. GREASE DAM 1/4"
- 11. 2" OPENING FOR AIR CIRCULATION
- 12. 36"ø GRADE-LEVEL MANWAY SHIPPED LOOSE
- 13. 24"ø PVC COVER
- 14. (2) 24"ø x 12" STACKABLE RISER ALL STACKABLE RISER COMPONENTS ARE PRE-ASSEMBLED AND COMPLETE MANWAY RISER IS SHIPPED LOOSE
- 15. (2) 24"ø x 6" STACKABLE RISER
- 16. STACKABLE RISER ADAPTER RING & GASKET
- 17. STACKABLE RISER SAFETY SCREEN
- 18. DIFFUSION BAFFLE 1/4"
- 19. 16" x 16" WEAR PLATE 1/4"
- 20. (6) CDA-15 CONCRETE DEADMAN
- 21. (6) POLYESTER HOLD-DOWN STRAPS



passive grease interceptor 5,000 GALLON TRIPLE-BASIN

CUSTOMER:

PROJECT:

PROJECT

QUOTE NO.:

NO.

DIMENSION TOLERANCE: ± 1" NTS 3/5/19 MGS PGI-5000-3