


NOTE: ALL RIGHTS RESERVED, THIS DRAWING MUST NOT BE REPRODUCED IN ANY FORM WITHOUT THE WRITTEN PERMISSION OF HIGHLAND TANK®. HIGHLAND TANK® SHALL BE RESPONSIBLE ONLY FOR ITEMS INDICATED ON THIS FABRICATION DRAWING UNLESS OTHERWISE NOTED. CUSTOMER IS RESPONSIBLE FOR VERIFYING CORRECTNESS OF SIZE AND COATINGS SHOWN ON THIS DRAWING.

GRADE LEVEL MANWAY NOT SHOWN THIS VIFW



NO. REQ. - -FNPT FITTING W/ 2" SCH 40 RISER PIPE (FOR LEGEND OPERATING PRESSURE - ATMOSPHERIC LEVEL SENSOR) TANK MATERIAL – MILD CARBON STEEL HTM SPIN BRK'T - MFG USE ONLY - NOT TO BE USED FOR FIELD INSTALLATION THICKNESS - HEADS- 1/4" FILL CONNECTION - RFSO 150# FLANGE w/ STD. THICKNESS — SHELL— 1/4" Н WEIGHT RISER PIPE & INTERNAL DROP PIPE TO WITH *GA THK. BASED ON 60" MAX. BURIAL DEPTH IN 6" OF TANK BOTTOM, MITER END 45" (FILL) CONSTRUCTION - FLAT FLANGED HEADS, LAP WELD INSIDE & OUTSIDE 24"Ø TIGHT BOLT MANWAY w/ 1" THK. EPDM GASKET TANK TEST - 5 PSIG MATERIAL & MANWAY EXTENSION

D 2" FNPT FITTING (MANWAY VENT)

RUNGS ON 12" SPACING

16" WIDE STAINLESS STEEL INTERNAL LADDER w/ 🖁

FNPT FITTING w/ GOOSENECK VENT (VENT CONNECTION) 24"ø TIGHT BOLT MANWAY w/ 1" THK. EPDM GASKET MATERIAL & MANWAY EXTENSION 2" FNPT FITTING (MANWAY VENT) 6" RFSO 150# FLANGE w/ ANTI-VORTEX PLATE PER NFPA 22 (SUCTION) 36"ø GRADE LEVEL MANWAY

M 12" Ø GRADE LEVEL MANWAY

UNLESS NOTED, TOLERANCES ARE +/- 1 HighDRO® WATER STORAGE TANK 6,000 GAL 96"Ø SINGLE-WALL UNDERGROUND HORIZONTAL FOR FIRE PROTECTION WITH BOTTOM DRAIN CUSTOMER: PROJECT: CHK'D BY:

QUOTE NO: 3/8"=1'-0" 06000HGSWHDFPTBD96

INT. FINISH - SP10 BLAST HighDRO®-LINER PLUS FOR NSF 61 APPLICATIONS EXT. FINISH - SP6 BLAST, 75 MILS POLYURETHANE LABEL - UL-1746 PART IV, HIGHGUARD

TYPE - SINGLE WALL, HIGHGUARD UNDERGROUND

1) THE HIGHGUARD TANK IS NOT APPROVED FOR THE STORAGE OF HEATED PRODUCTS. 2) 15,000 VOLT SPARK TEST PROVIDED AT FACTORY.
3) SHOP TO INSTALL 1/4"x12"x12" STRIKER PLATES, ROLLED AND SEAL WELD TO THE TANK.

DESIGN DATA

CAPACITY - 6,000 GALLONS