

DESIGN DATA
CAPACITY - 6,000 GALLONS
TYPE - SINGLE WALL, HIGHGUARD UNDERGROUND
NO. REQ. — —
OPERATING PRESSURE - ATMOSPHERIC
TANK MATERIAL - MILD CARBON STEEL
THICKNESS - HEADS- 7 GA THICKNESS - SHELL- 1/4"
*GA THK. BASED ON 60" MAX. BURIAL DEPTH
CONSTRUCTION — FLAT FLANGED HEADS, LAP WELD INSIDE & OUTSIDE
TANK TEST - 5 PSIG
INT. FINISH — SP10 BLAST HighDRO®—LINER Plus for NSF 61 Applications
EXT. FINISH - SP6 BLAST, 75 MILS POLYURETHANE

LABEL - UL-1746 PART IV, HIGHGUARD

- 1) THE HIGHGUARD TANK IS NOT APPROVED FOR THE
- TO THE HIGH BOARD LAWN IS NOT APPROVED FOR THE STORAGE OF HEATED PRODUCTS.

  2) 15,000 VOLT SPARK TEST PROVIDED AT FACTORY.

  3) SHOP TO INSTALL 1/4"x12"x12" STRIKER PLATES, ROLLED AND SEAL WELD TO THE TANK.

	LEGEND			
	Α	HTM SPIN BRK'T — MFG USE ONLY — NOT TO BE USED FOR FIELD INSTALLATION	G	2" FNPT FITTING
	В	24"Ø TIGHT BOLT MANWAY W/ 18" THK. EPDM GASKET MATERIAL.	Н	FNPT FITTING w/ GOOSENECK VENT (VENT CONNECTION)
	С	24"Ø MANWAY EXTENSION & COVER PLATE w/ 18" THK. EPDM GASKET	J	6" 150# RFSO FLANGE w/ ANTI-VORTEX PLATE (SUCTION)
	D	2" FULL COUPLING (ELECTRICAL CONNECTION)	K	LEVEL CONTROL MANWAY W/ 17 THK. EPDM GASKET MATERIAL, CONTINUOUS LEVEL AND/ OR FLOATS
	Е	16" WIDE INTERNAL LADDER W/ 3/4" RUNGS ON 12" SPACING.	L	2" FULL COUPLING (ELECTRICAL CONNECTION)
	F	FNPT FITTING PIPE WITH SCH 40 DROP TO WITHIN 6" OF TANK BOTTOM (FILL CONNECTION)		

