COATING: MATERIAL THICKNESS EXTERIOR-CHEMPRIME 3001 (3-6 MILS)

(2-3 MILS)CHEMLINE 3300 TOP COAT "WHITE"

(15 MILS)

NOTES

CHEMLINE 4200 PW

ALL INTERNAL MATERIAL IS 10 GA
 ALL THREADED DRAIN FITTINGS TO HAVE STEEL THREADED PLUGS AND COATED WITH TANK
 ALL OTHER THREADED FITTINGS TO HAVE PVC THREADED PLUGS
 LIFTING LUGS HAVE REINFORCING PLATES

INTERIOR-


12. (6) PIECE COVER W/ 5/8" BOLT HOLES - 7 GA

22. 6" THICK REMOVABLE PETROSCREEN CARTRIDGE COALESCER

25. 3/4" THICK LIFTING LUG ANGLED TOWARD CENTER

29. 2"ø FNPT HALF COUPLING (SPARE)





PROVIDED EQUIPMENT GENERAL SPECIFICATIONS NO. REQ'D: (1) CAPACITY: 6000 GALLONS 1. 3"X3"X1/4" FLAT W/ 9/16" HOLE DRILLED IN CENTER (GROUNDING LUG) SEDIMENT CHAMBÉR TYPE: RECTANGULAR, HTC, ABOVEGROUND, S-SERIES 3. OIL WATER SEPARATOR CHAMBER 4. 150# RFSO FLANGED INLET MATERIAL: MILD CARBON STEEL FLOW RATE: 600 GPM GAUGE: 1/4" THROUGHOUT SURFACE PREP: 5. STEËL INLET ELBOW PIPING (24)(23 (31) 6. VELOCITY HEAD DIFFUSION BAFFLE 10GA SSPC NO.10 BLAST ALL INTERIOR SURFACES 7. WEAR PLATE (1/4" MATERIAL) SSPC NO.6 BLAST ALL EXTERIOR SURFACES 8. REMOVABLE PARALLEL CORRUGATED PLATE COALESCER (CORELLA PVC PLATES) 1" PLATE SPACING COATING: MATERIAL **THICKNESS** SLUDGE BAFFLE - 10GA (19) EXTERIOR-CHEMPRIME 3001 (3-6 MILS)10. FLANGED PVC OUTLET DOWNCOMER PIPE CHEMLINE 3300 TOP COAT "WHITE" (2-3 MILS)11. 150# RFSO FLANGED OUTLET W/ INTERNAL STEEL ELBOW 18" (16) 12. (6) PIECE COVER W/ 5/8" BOLT HOLES - 7 GA 13. NUTS & BOLTS W/ LARGE WING (CORROSION RESISTANT) 14. GASKET MATERIAL (FOR EACH REMOVABLE COVER) CHEMLINE 4200 PW (15 MILS) INTERIOR-CONSTRUCTION: BUTT FIT AND WELD ALL CORNERS IN & OUT 15. 3"Ø FNPT (CLEAN-OUT) 16. 2"ø FNPT (VENT) 17. 2"ø FNPT (DRAIŃ) NOTES (18) 18. 3"Ø FNPT FULL COUPLING WITH 3" INTERNAL PVC PIPE (OIL PUMP OUT IN SEPERATOR CHAMBER) 19. 2"Ø FNPT (SEPARATOR CHAMBER INTERFACE LEVEL SENSOR) 20. 7GA. CROSSMEMBER FOR OIL PUMP—OUT & LEVEL SENSOR FITTINGS IN SEPARATOR AND OIL HOLDING CHAMBERS 1. ALL INTERNAL MATERIAL IS 10 GA 2. ALL THREADED DRAIN FITTINGS TO HAVE STEEL THREADED PLUGS AND COATED WITH TANK 3. ALL OTHER THREADED FITTINGS TO HAVE PVC THREADED PLUGS (25)4. LIFTING LUGS HAVE REINFORCING PLATES (23)(24) (16)(17)HANDLES PER H.T. STANDARD 22. 6" THICK REMOVABLE PETROSCREEN CARTRIDGE COALESCER 36 1/2" 48 1/2" 36 37" 37" 23. 10"ø STEEL ELBOW W/ FLANGE WELDED TO TOP FOR PVC RISER PIPES REMOVABLE COVERS (6) REQUIRED 24. 10"ø ADJUSTABLE FERNCO COUPLING 25. 3/4" THICK LIFTING LUG ANGLED TOWARD CENTER 26. 1"ø FNPT COUPLING W/ PLUG PIAN VIFW 27. OIL HOLDING COMPARTMENT 28. 3" FNPT COUPLING WITH SAWTOOTH TYPE PVC OIL SKIMMER & PIPE SUPPORT SHELF 29. 2"Ø FNPT HALF COUPLING (SPARE) 30. 2"Ø FNPT (HIGH LEVEL OIL HOLDING CHAMBER LEVEL SENSOR) 31. 3"Ø FNPT FULL COUPLING WITH 3" INTERNAL PVC PIPE (OIL PUMP OUT IN OIL HOLDING CHAMBER) 72" 36' (19)(18` 1" TYP. (12)(16) 6 14" 14" 26 (16 31 9' 8 (59) 4 ", 26" INLET OUTLET (3) 9 (2 REVISIONS 6 3" 18 18" 36" 22' 39" 36" 30" 24" 84" 6 54" 176" U.S. Patent #4,722,800 Canadian Patent # 1,296,263 6000 GALLON DIL WATER SEPARATOR 19'-2" -RECTANGULAR, HTC, S-SERIES FND VIFW CUSTOMER: ELEVATION PROJECT: NOTE: ALL RICHTS RESERVED. THIS DRAWING OR ANY PART THEREOF MUST NOT BE REPRODUCED IN ANY FORM WITHOUT THE WRITTEN PERMISSION OF HIGHLAND TANK. HIGHLAND TANK. OF HIGHLAND TANK SHALL BE RESPONSIBLE ONLY FOR ITEMS INDICATED ON THIS FABRICATION DRAWING UNLESS OTHERWISE NOTED. CUSTOMER IS RESPONSIBLE FOR VERIFYING CORRECTIVESS OF SIZE / LOCATION OF FITTINGS, ACCESSORIES & COATINGS SHOWN ON THIS DRAWING CHK'D BY: QUOTE NO: SCALE: DATE: 06000RECSWHTCS /4"=1'-0"