
NOTE: ALL RIGHTS RESERVED. THIS DRAWING MUST NOT BE REPRODUCED IN ANY FORM WITHOUT THE WRITTEN PERMISSION OF HIGHLAND TANK® HIGHLAND TANK® HIGHLAND TANK® SHALL BE RESPONSIBLE ONLY FOR ITEMS INDICATED ON THIS FABRICATION DRAWING UNLESS OTHERWISE NOTED. CUSTOMER IS RESPONSIBLE FOR VERIFYING CORRECTIVESS OF SIZE AND LOCATION OF FITTINGS, ACCESSORIES, AND COATINGS SHOWN ON THIS DRAWING.

TOUCH UP OF FINISHED PAINT IS REQUIRED BY INSTALLATION CONTRACTOR. TOUCH UP PAINT SHIPPED WITH TANK. SHIPPING LUGS AS NEEDED





DESIGN DATA		<u>LEGEND</u>
CAPACITY -8,000 GALLONS] A	FLANGE — SUPPLY
TYPE - POTABLE WATER TANK (PWT)		
NO. REQ	Bl	FLANGE – VENT
OPERATING PRESSURE -ATMOSPHERIC		24" X 4" PLATE TIGHT BOLT MANWAY WITH 8"
TANK MATERIAL - MILD CARBON STEEL	<u> </u>	THICK NEO-CORK GASKET
THICKNESS - HEADS: 5/16"	D	4" FNPT CONNECTION
THICKNESS - SHELL: 1/4"	\vdash	STD HTM EXTERNAL LADDER & PLATFORM
CONSTRUCTION - LAP WELD INSIDE AND OUTSIDE		ASSEMBLY — PAINTED SAFETY YELLOW AND SHIPPED LOOSE FOR INSTALLATION ON
TANK TEST -5 PSIG		SITE BY OTHERS
INT. FINISH - SP10 BLAST HighDRO®-LINER	F	HTM STD INTERNAL LADDER
PLUS FOR NSF 61 APPLICATIONS		FLANGE WITH INTERNAL 90° ELBOW
EXT. FINISH -SSPC SP6 BLAST, WHITE URETHANE PAINT		SHOWN — OVERFLOW
		FB-3"x 1/4"x3" WITH 5/8"Ø HOLE ON CL
LABEL – NONE	'''	(GROUNDING LUG)

