

NOTE: ALL RIGHTS RESERVED. THIS DRAWING MUST NOT BE REPRODUCED IN ANY FORM WITHOUT THE WRITTEN PERMISSION OF HIGHLAND TANK® HIGHLAND TANK® HIGHLAND TANK® SHALL BE RESPONSIBLE ONLY FOR ITEMS INDICATED ON THIS FABRICATION DRAWING UNLESS OTHERWISE NOTED. CUSTOMER IS RESPONSIBLE FOR VERIFYING CORRECTIVESS OF SIZE AND LOCATION OF FITTINGS, ACCESSORIES, AND COATINGS SHOWN ON THIS DRAWING.

TOUCH UP OF FINISHED PAINT IS REQUIRED BY INSTALLATION CONTRACTOR. TOUCH UP PAINT SHIPPED WITH TANK.





| DESIGN DATA | <u>LEGEND</u> |
|---|--|
| CAPACITY -10,000 GALLONS | A FLANGE - SUPPLY |
| TYPE — POTABLE WATER TANK (PWT) | |
| NO. REQ. – | B FLANGE — VENT |
| OPERATING PRESSURE — ATMOSPHERIC TANK MATERIAL — MILD CARBON STEEL | C 24" X ¼" PLATE TIGHT BOLT MANWAY WITH ½" THICK NEO-CORK GASKET |
| THICKNESS: HEADS - 5/16" THICKNESS: SHELL - 1/4" | D 4" FNPT CONNECTION |
| IHICKNESS: SHELL - 1/4 | STD HTM EXTERNAL LADDER & PLATFORM |
| CONSTRUCTION -LAP WELD INSIDE & OUTSIDE | E ASSEMBLY — PAINTED SAFETY YELLOW AND SHIPPED LOOSE FOR INSTALLATION ON |
| TANK TEST -5 PSIG | SITE BY OTHERS |
| NT. FINISH — SP10 BLAST HighDRO®—LINER PLUS FOR NSF 61 APPLICATIONS | F HTM STD INTERNAL LADDER |
| EXT. FINISH -SSPC SP6 BLAST, WHITE URETHANE | G FLANGE WITH INTERNAL 90° ELBOW |
| PAINT PAINT | SHOWN - OVERFLOW |
| LABEL - NONE | H FB-3"x 1/4"x3" WITH 5/8"Ø HOLE ON CL (GROUNDING LUG) |
| | |

