





GRADE LEVEL

<u>DESIGN DATA</u>				
CAPACITY - 15,000 GALLONS				
TYPE - SINGLE WALL, HIGHGUARD UNDERGROUND				
NO. REQ. — —				
OPERATING PRESSURE - ATMOSPHERIC				
TANK MATERIAL - MILD CARBON STEEL				
THICKNESS - HEADS- 5/16" THICKNESS - SHELL- 5/16"				
*GA THK. BASED ON 60" MAX. BURIAL DEPTH				
CONSTRUCTION — FLAT FLANGED HEADS, LAP WELD INSIDE & OUTSIDE				
TANK TEST - 5 PSIG				
INT. FINISH — SP10 BLAST HighDRO®—LINER Plus for NSF 61 applications				
EXT. FINISH - SP6 BLAST, 75 MILS POLYURETHANE				
LABEL — UL—1746 PART IV, HIGHGUARD				

- NOTES:

 1) THE HIGHGUARD TANK IS NOT APPROVED FOR THE STORAGE OF HEATED PRODUCTS.

 2) 15,000 VOLT SPARK TEST PROVIDED AT FACTORY.

 3) SHOP TO INSTALL 1/4"x12"x12" STRIKER PLATES, ROLLED AND SEAL WELD TO THE TANK.

LEGEND		F	2" FNPT FITTING W/ 2" SCH 40 RISER PIPE (FOR LEVEL SENSOR)
Α	HTM SPIN BRK'T — MFG USE ONLY — NOT TO BE USED FOR FIELD INSTALLATION	G	FNPT FITTING W/ GOOSENECK VENT (VENT CONNECTION)
В	WEIGHT RISER PIPE & INTERNAL DROP PIPE TO WITH	Н	24"Ø TIGHT BOLT MANWAY W/ 8" THK. EPDM GASKET MATERIAL & MANWAY EXTENSION
	IN 6" OF TANK BOTTOM, MITER END 45" (FILL)	J	2" FNPT FITTING (MANWAY VENT)
С	24"Ø TIGHT BOLT MANWAY W/ 8" THK. EPDM GASKET MATERIAL & MANWAY EXTENSION	K	6" RFSO 150# FLANGE w/ ANTI-VORTEX PLATE PER NFPA 22 (SUCTION)
D	2" FNPT FITTING (MANWAY VENT)	L	36"Ø GRADE LEVEL MANWAY
Е	16" WIDE STAINLESS STEEL INTERNAL LADDER W/ 3" RUNGS ON 12" SPACING	М	12"Ø GRADE LEVEL MANWAY



HighDRO® WATER STORAGE TANK 15,000 GAL 96" SINGLE-WALL UNDERGROUND HORIZONTAL FOR FIRE PROTECTION WITH BOTTOM DRAIN

1/4"=1'-0"

15000HGSWHDFPTBD96