

OPERATING PRESSURE - ATMOSPHERIC SPECIFIC GRAVITY = 1.0 TANK MATERIAL - MILD CARBON STEEL 10" FFSO 150# FLANGE - FOR PRIMARY В 8" FEMALE FIREGUARD COUPLING THICKNESS - INNER - HEADS: 5/16", SHELL: 1/4" EMERGENCY VËNT USE ONLY THICKNESS - OUTER - HEADS: 5/16", SHELL: 1/4" 10" FFSO 150# FLANGE THROUGH OUTER SHELL ONLY, 10" SCH 40 PIPE MIN. GAUGE OR THICKNESS (PER U.L. 2085) MARK WITH SPECIAL WARNING LABEL INTERSTITIAL CONSTRUCTION - INNER - LAP WELD OUTSIDE ONLY EMERGENCY VENT USE ONLY Κ 2" FEMALE FIREGUARD COUPLING CONSTRUCTION — OUTER — LAP WELD OUTSIDE ONLY 2" FITTING THROUGH OUTER SHELL ONLY WITH CAST TANK TEST - PER UL 2085 IRON PLUG- MFG USE ONLY L 2" INTERSTITIAL MONITOR PIPE - MALE INT. FINISH - NONE NPT END EXT. FINISH - SP-6 BLAST, FINISH PAINT WHITE 24" x 1/4" PLATE TIGHT BOLT MANWAY WITH 1/8" THICK NEO-CORK GASKET LABEL- UL 2085 AND FIREGUARD® PER sti

PROJECT:

QUOTE NO:

SCALE: | DATE: | DWG. BY: | 20000FGCYL1200P