

TOUCH UP OF FINISHED PAINT IS
REQUIRED BY INSTALLATION
CONTRACTOR. TOUCH UP PAINT SHIPPED
WITH TANK.

LEGEND

A	4" FITTING
B	24"Ø TIGHT BOLT MANWAY w/ 1" FIBREFLEX GASKET
C	2" FNPT FITTING (2 REQ'D) IN OPPOSITE CORNERS OF THE DIKE
D	10" 150# FFSO FLANGE – PRIMARY EMERGENCY VENT USE

TANK DESIGN DATA

CAPACITY – 30,000 GALLONS
TYPE – ABOVEGROUND HORIZONTAL WITH 110% DIKE
NO. REQ. – –
OPERATING PRESSURE – ATMOSPHERIC
SPECIFIC GRAVITY = 1.0
TANK MATERIAL – MILD CARBON STEEL
THICKNESS – HEADS – 5/16"
THICKNESS – SHELL – 1/4"
CONSTRUCTION – LAP WELD OUTSIDE ONLY
TANK TEST – 5 PSIG
INT. FINISH – NONE
EXT. FINISH – SHOP PRIMER
LABEL – UL 142

DIKE DESIGN DATA

CAPACITY – 33,000 GALLONS
TANK MATERIAL – MILD CARBON STEEL
THICKNESS – ALL – 1/4"
CONSTRUCTION – WELDED INSIDE & OUT
FINISH – ALL – SAME AS TANK EXTERIOR

